

Special Products / Extreme Environments

SUMITUBE® Product Series	Product Description	Industry Certifications & Approvals	AS23053 Slash Sheet	Shrink Ratio	Shrink Temp Minimum	Operating Temp Range	Colors	Size Range
DPX-1 Tape	Thermoplastic Adhesive Tape (Hot Melt)	RoHS		N/A	N/A	-55°C to +110°C	Translucent Amber	50mm 1.97" Width
FE3	High Temperature Flexible Fluoroelastomer	RoHS	/13	2:1	120°C	-40°C to +200°C	Black, Red, Blue, Yellow, White	1/8" to 2"
K	Semi-Rigid High Temperature Translucent PVDF	UL/CSA/RoHS	/8	2:1	170°C	-55°C to +175°C	Translucent	3/64" to 2"
K2	Flexible High Temperature Clear PVDF	UL/RoHS	/18 Class 1	2:1	150°C	-55°C to +175°C	Clear	3/64" to 2"
K3	Very Flexible High Temperature Clear Modified Fluoropolymer	UL/RoHS	/18 Class 3	2:1	130°C	-55°C to +150°C	Clear	1/8" to 1"
KH200	Very Flexible High Temp Fluoropolymer	UL/RoHS	/13	2:1	130°C	-70°C to +200°C	Clear	1/8" to 1"
KH200 (TW)	Very Flexible High Temp Fluoropolymer Thin Wall	UL/RoHS	/18 Class 3	2:1	130°C	-70°C to +200°C	Clear	1/8" to 1"
KH230	Very Flexible High Temp Fluoropolymer Thin Wall	RoHS	/13	2:1	130°C	-70°C to +230°C	Black	1/8" to 1"
KH230 (TW)	Very Flexible High Temp Fluoropolymer Thin Wall	RoHS	/18 Class 3	2:1	130°C	-70°C to +230°C	Black	1/8" to 1"
R10	Fluid Resistant Elastomer	UL/RoHS	/1 Class 1 & 2	2:1	150°C	-70°C to +121°C	Black	1/8" to 2"
R120	Enhanced Fluid Resistant Elastomer	RoHS	/16	2:1	150°C	-75°C to +120°C	Black	1/8" to 2"

