# ZHTM-3/1.5-0-SP ✓ ACTIVE

#### **RAYCHEM**

TE Internal #: 2411034003

Black, 2:1, Shrinks To .059 in [1.5 mm], Chlorinated Polyolefin, Pre-Coated Wrap Jacket Wall Material, .118 in [3 mm] Inner Diameter,

Flame-Retardant

View on TE.com >



Heat Shrink Tubing > ZHTM: Heat Shrink Tubing, 2:1 Shrink Ratio



Primary Product Color: Black

Wall Material Type: Pre-Coated Wrap Jacket

Expanded Inside Diameter (Min): 3 mm [.118 in ]

Recovered Inside Diameter (Max): 1.5 mm [.059 in ]

Shrink Ratio: 2:1

All ZHTM: Heat Shrink Tubing, 2:1 Shrink Ratio (9)

### **Features**

### **Product Type Features**

Wall Material Type	Pre-Coated Wrap Jacket
Body Features	
Fluid Type	Brake Fluid, Diesel Fuel, Hydraulic Fluid, Insulating Oil, Lubricating Oil, Unleaded Gasoline, Water
Material Systems Code	100
Primary Product Color	Black
Shrink Ratio	2:1
Primary Product Material	Chlorinated Polyolefin
Flexibility	Flexible
Dimensions	
Recovered Wall Thickness (Nominal)	.7 mm[.028 in]
Expanded Inside Diameter (Min)	3 mm[.118 in]
Recovered Inside Diameter (Max)	1.5 mm[.059 in]
Tubing Size Range	1.5 – 3 mm[.059 – .118 in]
Usage Conditions	
Shrink Temperature (Min)	121 °C



Tubing Flammability Type	Flame-Retardant
Operating Temperature Range	-30 – 105 °C
Recovery Temperature	121 °C
Operation/Application	
Mechanical Resistance	Mechanical Damage
Packaging Features	
Packaging Method	Piece
Other	
Meets Low Outgassing Requirements	No
Product Source	US

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Customers Also Bought





















## **Documents**

Product Drawings
ZHTM-3/1.5-0-SP

English

Datasheets & Catalog Pages

raychem-tubing-product-selection-guide

English

1654025\_Sec3\_ZHTM

English

**Product Specifications** 

Thermofit Zerohal ZHTM Tubing Elastomeric, Halgen-Free, Flame-Retarded, Flexible, Heat-Shrinkable

English

**ZHTM SLEEVING** 

English

**Instruction Sheets** 

Instruction Sheet (U.S.)

English

Black, 2:1, Shrinks To .059 in [1.5 mm], Chlorinated Polyolefin, Pre-Coated Wrap Jacket Wall Material, .118 in [3 mm] Inner Diameter, Flame-Retardant

