

Dual Wall Adhesive Lined Tubing

Dual Wall Tubing is designed to environmentally seal and protect electrical and power distribution applications and connector - to cable transitions.

Material: Polyolefin

Colors: Black

Shrink Ratio: 3:1 (3:1 with no adhesive is available on special order - contact sales department)

Operating Temperature: -55°C to 125°C

Certifications: UL224 125 degree. C VW1, CSA C22.2 NO 198.1 OFT

Voltage: 600V

| HOFFMAN PART NO. | INSIDE DIAMETER | | | | NOMINAL RECOVERED WALL THICKNESS | | | | REEL QTY | 4 FOOT PKG QTY | 6 INCH PKG QTY |
|------------------|------------------------------|-------|------------------------------|-------|----------------------------------|-------|-----------------------------|-------|----------|----------------|----------------|
| | MINIMUM EXPANDED AS SUPPLIED | | MAXIMUM RECOVERED AFTER HEAT | | TOTAL WALL AFTER HEATING | | ADHESIVE WALL AFTER HEATING | | | | |
| | MM | IN | MM | IN | MM | IN | MM | IN | | | |
| HSTBD1/8 | 3.20 | 0.126 | 1.00 | 0.039 | 0.95 | 0.037 | 0.35 | 0.014 | 500 | 25 | 28 |
| HSTBD3/16 | 4.80 | 0.189 | 1.60 | 0.063 | 1.10 | 0.043 | 0.40 | 0.016 | 300 | 25 | 24 |
| HSTBD1/4 | 6.40 | 0.252 | 2.20 | 0.087 | 1.20 | 0.047 | 0.45 | 0.018 | 300 | 25 | 20 |
| HSTBD5/16 | 7.90 | 0.311 | 2.70 | 0.106 | 1.35 | 0.053 | 0.50 | 0.020 | 250 | 25 | 18 |
| HSTBD3/8 | 9.50 | 0.374 | 3.20 | 0.126 | 1.45 | 0.057 | 0.50 | 0.020 | 150 | 25 | 16 |
| HSTBD1/2 | 12.70 | 0.500 | 4.20 | 0.165 | 1.70 | 0.067 | 0.50 | 0.020 | 100 | 5 | 14 |
| HSTBD3/4 | 19.10 | 0.752 | 6.30 | 0.248 | 2.00 | 0.079 | 0.55 | 0.022 | 100 | 5 | 12 |
| HSTBD1 | 25.40 | 1.000 | 8.50 | 0.335 | 2.10 | 0.083 | 0.55 | 0.022 | 100 | 5 | 8 |
| HSTBD1.5 | 39.00 | 1.535 | 13.50 | 0.531 | 2.40 | 0.094 | 0.60 | 0.024 | 50 | 5 | 5 |

Medium Wall Adhesive Lined Tubing

This tubing has a hot melt adhesive liner which creates a strong bond between the cable jacket and the tube. Designed for use in aerial and underground applications.

Material: Polyolefin

Colors: Black

Shrink Ratio: 3:1

Operating Temperature: -55°C to +110°C

Certifications: UL224 125 degree. C VW1, CSA C22.2 NO 198.1 OFT

Voltage: 600V

| HOFFMAN PART NO. | INSIDE DIAMETER | | | | NOMINAL RECOVERED WALL THICKNESS AFTER HEATING | |
|------------------|------------------------------|-------|------------------------------|-------|--|-------|
| | MINIMUM EXPANDED AS SUPPLIED | | MAXIMUM RECOVERED AFTER HEAT | | MM | IN |
| | MM | IN | MM | IN | | |
| HSTM12 | 12 | 0.472 | 3 | 0.118 | 2.0 | 0.079 |
| HSTM22 | 22 | 0.866 | 6 | 0.236 | 2.5 | 0.098 |
| HSTM28 | 28 | 1.102 | 6 | 0.236 | 2.5 | 0.098 |
| HSTM33 | 33 | 1.299 | 8 | 0.315 | 2.5 | 0.098 |
| HSTM40 | 40 | 1.575 | 12 | 0.472 | 2.5 | 0.098 |
| HSTM55 | 55 | 2.165 | 16 | 0.630 | 2.7 | 0.106 |
| HSTM65 | 65 | 2.559 | 19 | 0.748 | 2.8 | 0.110 |
| HSTM75 | 75 | 2.953 | 20 | 0.787 | 3.0 | 0.118 |
| HSTM95 | 95 | 3.740 | 25 | 0.984 | 3.0 | 0.118 |
| HSTM115 | 115 | 4.528 | 34 | 1.339 | 3.0 | 0.118 |

Sold in 1.2 Meter Pieces Only

