BGA Heat Sink (High Aspect Ratio Ext.) Straight Fin





ATS Part#: Description: ATS012012010-SF-2I

12.00 x 12.00 x 10.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Straight Fin

 Heat Sink Type:
 Straight Fin

 Heat Sink Attachment:
 N/A

 Equivalent Part Number:
 N/A

*Image above is for illustration purpose only.

Features & Benefits

- · High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- · Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	23.7 °C/W	19.1 °C/W	16.6 °C/W	15 °C/W	13.7 °C/W	12.8 °C/W	12 °C/W
	Ducted Flow	15.5	13.1	11.6	10.6	9.8	9.2	8.6

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	тім	Finish
Mar	12.00 mm	12.00 mm	10.00 mm	12 mm	N/A	BLACK-ANODIZED
Image above is for illustration purpose only.	 Dimension Dimension Thermal p application ATS resent performant ATS certifier 	n D is fin tip to fin tip performance data are n. rves the right to upda nce.	e provided for refere ate or change its pro k assembly is RoHS	m of the base to the nce only. Actual perf ducts without notice 6-6 and REACH com ble.	formanc to impr	e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA