BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin



ATS Part#: ATS015015006-PF-4E

Description: 15.00 x 15.00 x 6.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin



Heat Sink Type: Custom Pin Fin

Heat Sink Attachment: N/A Equivalent Part Number: N/A

*Image above is for illustration purpose only.

Features & Benefits

- · High efficiency pin fin design provides low pressure drop characteristics
- · Large surface area increases heat sink performance
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- · Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	33.59 °C/W	27.7 °C/W	24.2 °C/W	21.9 °C/W	20.1 °C/W	18.8 °C/W	17.6 °C/W
	Ducted Flow	20.8	17.5	15.5	14	12.9	12.1	11.4

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
nln	15.00 mm	15.00 mm	6.00 mm	15 mm	N/A	BLACK-ANODIZED
*Image above is for illustration purpose only.	Dimension Dimension Thermal papplication ATS reserved performar ATS certification ATS certification	n D is fin tip to fin tip performance data are n. rves the right to upd nce.	e provided for reference or change its prokate or change its prokate wassembly is RoHS	m of the base to the nce only. Actual perioducts without notices -6 and REACH comble.	formand to impr	e may vary by

