

Han-Eco Mod.6-C-f. HTE/HSE



Image is for illustration purposes only. Please refer to product description.

Part number	19 41 006 5406
Specification	Han-Eco Mod.6-C-f. HTE/HSE
HARTING eCatalogue	https://b2b.harting.com/19410065406

Identification

Category	Accessories
Series of hoods/housings	Han-Eco® Modular
Type of accessory	Protection cover
Description of the accessory	for hoods

Version

Size	6 B
Locking type	Double locking lever

Technical characteristics

Limiting temperature	-40 ... +125 °C
Number of relockings	≥500
Degree of protection acc. to IEC 60529	IP65

Material properties

Material (hood/housing)	Polyamide (PA) Fibre-glass reinforced
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Colour (seal)	RAL 9005 (jet black)
Material (locking)	Polyamide (PA) Fibre-glass reinforced
Colour (locking)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0



Pushing Performance
Since 1945

Material properties

Material flammability class acc. to UL 94
(locking levers)

V-0

RoHS

compliant

ELV status

compliant

China RoHS

e

REACH Annex XVII substances

Not contained

REACH ANNEX XIV substances

Not contained

REACH SVHC substances

Not contained

California Proposition 65 substances

Yes

California Proposition 65 substances

Naphthalene

Fire protection on railway vehicles

EN 45545-2 (2020-08)

Requirement set with Hazard Levels

R22 (HL 1-3)

R23 (HL 1-3)

Specifications and approvals

Specifications

IEC 61984

EN 45545-2 Fire protection on railway vehicles

UL / CSA

UL 1977 ECBT2.E235076

CSA-C22.2 No. 182.3 ECBT8.E235076

Commercial data

Packaging size

1

Net weight

63.6 g

Country of origin

Germany

European customs tariff number

85389099

GTIN

5713140130821

ETIM

EC002314

eCl@ss

27440208 Cap for industrial connectors