#### 1645998

https://www.phoenixcontact.com/us/products/1645998

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Metal screw connection up to 5 bar, thread length: 6 mm, cable diameter: 11 - 16 mm, WAF 27, screw connection: M20

## Commercial data

Item number	1645998
Packing unit	25 pc
Minimum order quantity	25 pc
Sales key	BF68
Product key	BF7DAX
Catalog page	Page 690 (C-4-2015)
GTIN	4017918941260
Weight per piece (including packing)	46.75 g
Weight per piece (excluding packing)	45.51 g
Customs tariff number	74198090
Country of origin	DE

PHŒNIX

1645998

https://www.phoenixcontact.com/us/products/1645998



## Technical data

### Product properties

Product type	Cable screw gland
Application	Standard
No. of conductors	1
Manufacturer	Jacob
Manufacturer Designation	50.620/25 M
Shielded	no

#### Dimensions

Dimensional drawing



Length	35.5 mm
Length of the connecting thread	6 mm
Hole diameter	20.1 mm 20.2 mm
Wrench size, union nut	27 mm
Wrench size, support	27 mm
Hexagon angular dimension	30 mm
Thread type connection side	M20 x 1.5
Thread pitch	1.5 mm

### Material specifications

Material Compression ring	PA
Seal material O-ring	NBR
Seal material Cable seal	CR/NBR
Material for screw connection	Brass, nickel-plated

### Cable/line

External cable diameter Cable 1	11 mm 16 mm
Halogen-free	no

### Environmental and real-life conditions

Degree of protection	IP68 (up to 5 bar)
Ambient temperature (operation)	-30 °C 100 °C


1645998

https://www.phoenixcontact.com/us/products/1645998



## Drawings

Dimensional drawing



Dimensional drawing

1645998

https://www.phoenixcontact.com/us/products/1645998



## Classifications

### ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140801

## ETIM

	ETIM 9.0	EC000441
UNSPSC		
	UNSPSC 21.0	39121300

1645998

https://www.phoenixcontact.com/us/products/1645998



## Environmental product compliance

#### EU RoHS

Yes
6(c)
EFUP-50
An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
Lead(CAS: 7439-92-1)
b4f45b5a-e88d-4bc0-87dc-337c28da4a9f

1645998

https://www.phoenixcontact.com/us/products/1645998



Accessories

A-INL-M20-N-S - Counter nut

1411242 https://www.phoenixcontact.com/us/products/1411242

Counter nut, for threads M20 x 1.5, color: silver



## SEALING PLUG 13X22 RD - Closing cap

1400265

https://www.phoenixcontact.com/us/products/1400265



Closing cap, color: red

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com