

# Han TC100-HMC-MC-CRT-35 mm<sup>2</sup>-AU



Part number	09 11 200 6135
Specification	Han TC100-HMC-MC-CRT-35 mm <sup>2</sup> -AU
HARTING eCatalogue	https://b2b.harting.com/09112006135

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Contacts
Series	TC 100
Type of contact	Crimp contact
Features	lead-free

### Version

Gender	Male
Manufacturing process	Turned contacts

# Technical characteristics

Conductor cross-section	35 mm²
Rated current	≤100 A
Contact resistance	≤0.3 mΩ
Stripping length	16 mm
Limiting temperature	-40 +125 °C
Mating cycles with other HMC components	≥10,000

# Material properties

Material (contacts)	Copper alloy
Surface (contacts)	HMC gold plated
RoHS	compliant
ELV status	compliant
China RoHS	e

Page 1 / 2 | Creation date 2024-02-10 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 09 11 200 6135 Han TC100-HMC-MC-CRT-35 mm<sup>2</sup>-AU



#### Material properties

Specifications and approvals			
REACH SVHC substances	Not contained		
REACH ANNEX XIV substances	Not contained		
REACH Annex XVII substances	Not contained		

#### Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
Commercial data	

# Packaging size10Net weight22.6 gCountry of originGermanyEuropean customs tariff number85359000GTIN5713140188266ETIMEC00796eCl@ss27440204 Contact for industrial connectors