

## Han 48HPR hood



Image is for illustration purposes only. Please refer to product description.

Part number	09 40 048 0451
Specification	Han 48HPR hood
HARTING eCatalogue	<a href="https://b2b.harting.com/09400480451">https://b2b.harting.com/09400480451</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> HPR
Type of hood/housing	Hood

### Version

Size	48 B
Version	Top entry
Locking type	Screw locking
Field of application	Hoods/housings for harsh outdoor environments

### Technical characteristics

Tightening torque (screw locking)	4 Nm
Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65 IP68 IP69 / IPX9K acc. to ISO 20653

### Material properties

Material (hood/housing)	Aluminium die-cast Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (locking)	Stainless steel



Pushing Performance  
Since 1945

## Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R1 (HL 1-3) R7 (HL 1-3)

## Specifications and approvals

Specifications	IEC 61373 Category 1 Class B
CE	Yes
Approvals	DNV GL

## Commercial data

Packaging size	1
Net weight	1,440 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140058354
ETIM	EC000437
eCl@ss	27440202 Shell for industrial connectors