

# Han-Yellock 30 HSM 2xM20



| Part number        | 11 12 300 1204                      |
|--------------------|-------------------------------------|
| Specification      | Han-Yellock 30 HSM 2xM20            |
| HARTING eCatalogue | https://b2b.harting.com/11123001204 |

Image is for illustration purposes only. Please refer to product description.

#### Identification

| Category                 | Hoods/Housings              |
|--------------------------|-----------------------------|
| Series of hoods/housings | Han-Yellock <sup>®</sup>    |
| Type of hood/housing     | Surface mounted housing     |
| Version                  |                             |
| Locking type             | Screw locking               |
| Size                     | Han-Yellock <sup>®</sup> 30 |
| Version                  | Side entry                  |
| Cable entry              | 2x M20                      |

### **Technical characteristics**

Field of application

| Limiting temperature                   | -40 +125 °C |
|--|-------------|
| Un-/locking temperature                | -10 +85 °C  |
| Degree of protection acc. to IEC 60529 | IP65        |
|  | IP67        |

Hoods/housings for industrial applications

#### Material properties

| Material (hood/housing)                   | Aluminium die-cast    |
|---|-----------------------|
| Surface (hood/housing)                    | Powder-coated         |
| Colour (hood/housing)                     | RAL 7021 (black grey) |
| Material (seal)                           | NBR                   |
| Material flammability class acc. to UL 94 | V-0                   |

Page 1 / 2 | Creation date 2021-02-25 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



#### Material properties

| RoHS                        | compliant |
|-----------------------------|-----------|
| ELV status                  | compliant |
| China RoHS                  | e         |
| REACH Annex XVII substances | No        |
| REACH ANNEX XIV substances  | No        |
| REACH SVHC substances       | No        |

#### Specifications and approvals

| Specifications | EN 60664-1<br>IEC 61984 |
|----------------|-------------------------|
| Approvals      | DNV GL                  |
| CE             | Yes                     |

## Commercial data

| Packaging size                 | 1  |
|--------------------------------|--|
| Net weight                     | 414 g                                    |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |