

Han 16M-HSM2-DL-M25



Image is for illustration purposes only. Please refer to product description.

Part number	19 37 016 1271
Specification	Han 16M-HSM2-DL-M25
HARTING eCatalogue	https://b2b.harting.com/19370161271

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] M
Type of hood/housing	Surface mounted housing
Type	Low construction

Version

Size	16 B
Version	Side entry
Cable entry	2x M25
Locking type	Double locking lever
Field of application	Hoods/housings for rough environments

Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)



Pushing Performance
Since 1945

Material properties

Material (seal) FPM

Material (locking) Stainless steel

Specifications and approvals

UL / CSA UL 1977 ECBT2.E235076
CSA-C22.2 No. 182.3 ECBT8.E235076

Approvals CE
DNV GL

Commercial data

Packaging size 1

Net weight 290 g

Country of origin Germany

European customs tariff number 85389099

GTIN 5713140171244

ETIM EC000437

eCl@ss 27440202 Shell for industrial connectors