

## Han-Eco 24B-HSM2-for DL-M40 w. cov.-gl.



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 19 43 124 0268  |
| Specification      | Han-Eco 24B-HSM2-for DL-M40 w. cov.-gl.   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19431240268">https://b2b.harting.com/19431240268</a> |

### Identification

|                             |  |
|-----------------------------|--|
| Category                    | Hoods/Housings   |
| Series of hoods/housings    | Han-Eco® B   |
| Type of hood/housing        | Surface mounted housing                                  |
| Description of hood/housing | With thermo-plastic cover<br>With integrated cable gland |

### Version

|              |                                    |
|--------------|------------------------------------|
| Size         | 24 B                               |
| Version      | Side entry                         |
| Cable entry  | 2x M40                             |
| Locking type | Double locking lever (on the hood) |

### Technical characteristics

|  |  |
|--|--|
| Limiting temperature                   | -40 ... +125 °C                                |
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Number of relockings                   | ≥500   |
| Degree of protection acc. to IEC 60529 | IP66   |
| Clamping range                         | 16 ... 28 mm                                   |

### Material properties

|                         |  |
|-------------------------|--|
| Material (hood/housing) | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (hood/housing)   | RAL 9005 (jet black)                     |
| Material (seal)         | NBR                                      |



**Pushing Performance**  
 Since 1945

## Material properties

|   |                      |
|---|----------------------|
| Colour (seal)                             | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0                  |
| RoHS                                      | compliant            |
| ELV status                                | compliant            |
| China RoHS                                | e                    |
| REACH Annex XVII substances               | Not contained        |
| REACH ANNEX XIV substances                | Not contained        |
| REACH SVHC substances                     | Not contained        |
| California Proposition 65 substances      | Yes                  |
| California Proposition 65 substances      | Naphthalene          |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels        | R22 (HL 1-3)         |
|   | R23 (HL 1-3)         |

## Specifications and approvals

|                |  |
|----------------|--|
| Specifications | IEC 61984                                      |
|                | EN 45545-2 Fire protection on railway vehicles |
| Approvals      | CE   |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140180703                            |
| ETIM                           | EC000437                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |