

1419247

https://www.phoenixcontact.com/us/products/1419247

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Coupling housings D7, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PA, cable outlets: 1, straight, 1x M25, height: 60.5 mm, cable gland: none, protective cover: yes, Standard, for pin inserts

Commercial data

Item number	1419247
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APF
Catalog page	Page 517 (C-2-2019)
GTIN	4055626159782
Weight per piece (including packing)	43.6 g
Weight per piece (excluding packing)	43.6 g
Customs tariff number	85389099
Country of origin	CN



1419247

https://www.phoenixcontact.com/us/products/1419247

Technical data

Notes

General	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05,
	Q07, Q12

Product properties

Product type	Housing with locking latch
Housing type	Coupling housings
Product family	HC-STA-D07
Application	Standard
Туре	D7
No. of cable outlets	1
Type of the screw connection	1x M25
Protective cover	yes
Shielded	no
Cable outlet	straight
Pg screw connection	none

Dimensions

Dimensional drawing	34.2
Width	34.2 mm
Height	60.5 mm
Length	24.2 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
	V0 (Protective cover)
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material, protective cover	PA
Locking latch material	PA
Impact strength	IK06

Mechanical properties

Mechanical data

Type of the screw connection	1x M25
Locking type	Latch



1419247

https://www.phoenixcontact.com/us/products/1419247

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
Impact strength	IK06
Ambient temperature (operation)	-40 °C 125 °C




1419247

https://www.phoenixcontact.com/us/products/1419247

Drawings

Dimensional drawing



Dimensional drawing



1419247

https://www.phoenixcontact.com/us/products/1419247

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1419247

Approval ID: TAE000037S



EAC

Approval ID: RU C-DE.BL08.B.00511



cUL RecognizedApproval ID: E255026





UL Recognized
Approval ID: E255026

cULus Recognized



1419247

https://www.phoenixcontact.com/us/products/1419247

Classifications

UNSPSC 21.0

ECLASS

27440202
27440202
27440202
EC000437

31261500



1419247

https://www.phoenixcontact.com/us/products/1419247

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E

No hazardous substances above the limits

FU	REACH SVHC	



1419247

https://www.phoenixcontact.com/us/products/1419247

Accessories

G-INS-M25-M68N-NNES-S - Cable gland

1411165

https://www.phoenixcontact.com/us/products/1411165



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 11 mm \dots 17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver, with O-ring

G-INSEC-M25-S68N-NCRS-S - Cable gland

1411190

https://www.phoenixcontact.com/us/products/1411190



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 11 mm \dots 16 mm, shielding: yes, connecting thread: M25 x 1.5, color: silver, with O-ring



1419247

https://www.phoenixcontact.com/us/products/1419247

G-INS-M25-M68N-PNES-GY - Cable gland

1411126

https://www.phoenixcontact.com/us/products/1411126



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 11 mm \dots 17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver-grey RAL 7001

G-INS-M25-M68N-PNES-BK - Cable gland

1411134

https://www.phoenixcontact.com/us/products/1411134



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 11 mm \dots 17 mm, shielding: no, connecting thread: M25 x 1.5, color: jet black RAL 9005




1419247

https://www.phoenixcontact.com/us/products/1419247

US-EMLP (20X9) CUS - Plastic label

0830085

https://www.phoenixcontact.com/us/products/0830085





HC-D07-SL-PLBK - Housing brackets

1424440

https://www.phoenixcontact.com/us/products/1424440

Replacement latch for HC-D7 housing





1419247

https://www.phoenixcontact.com/us/products/1419247

HC-STA-D07-BCLFS-PLR-BK - Protective cover

1419270

https://www.phoenixcontact.com/us/products/1419270



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 29.4 mm, seal: yes, Standard, with lanyard, for socket inserts

HC-STA-D07-BCLFS-PL-BK - Protective cover

1419271

https://www.phoenixcontact.com/us/products/1419271

Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 29.4 mm, seal: no, Standard, with lanyard, for pin inserts





1419247

https://www.phoenixcontact.com/us/products/1419247

HC-STA-D07-BCSFS-PLR-BK - Protective cover

1419272

https://www.phoenixcontact.com/us/products/1419272



Protective cover D7, for single locking latch, protective cover material: PA, height: 30 mm, seal: yes, Standard, with lanyard, for socket inserts

HC-STA-D07-BCSFS-PL-BK - Protective cover

1419273

https://www.phoenixcontact.com/us/products/1419273



Protective cover D7, for single locking latch, material: PA, protective cover material: PA, height: 30 mm, seal: no, Standard, with lanyard, for pin inserts



1419247

https://www.phoenixcontact.com/us/products/1419247

WP-G HF IP66 M25 BK - Screw connection

3240899

https://www.phoenixcontact.com/us/products/3240899



Cable gland, metric thread, IP66 protection, straight

WP-G HF IP69K M25 BK - Screw connection

3240885

https://www.phoenixcontact.com/us/products/3240885



Cable gland, metric thread, IP68/69k protection, straight



1419247

https://www.phoenixcontact.com/us/products/1419247

WP-GA HF IP66 M25 BK - Screw connection

3240927

https://www.phoenixcontact.com/us/products/3240927

Cable gland, metric thread, IP66 protection, angled



WP-GA HF IP69K M25 BK - Screw connection

3240913

https://www.phoenixcontact.com/us/products/3240913

Cable gland, metric thread, IP68/69k protection, angled





1419247

https://www.phoenixcontact.com/us/products/1419247

WP-GR HF IP66 M25 BK - Screw connection

3240955

https://www.phoenixcontact.com/us/products/3240955



Cable gland, metric thread, IP66 protection, with strain relief

WP-GR HF IP69K M25 BK - Screw connection

3240941

https://www.phoenixcontact.com/us/products/3240941



Cable gland, metric thread, IP68/69k protection, with strain relief



1419247

https://www.phoenixcontact.com/us/products/1419247

WP-G PP HF M25 - Screw connection

3240999

https://www.phoenixcontact.com/us/products/3240999



Cable gland made from PP with metric thread, IP65 protection

WP-GT PP HF M25 - Screw connection

3241013

https://www.phoenixcontact.com/us/products/3241013



Cable gland made from PP with metric thread, rotatable, IP54 protection



1419247

https://www.phoenixcontact.com/us/products/1419247

WP-G BRASS IP40 M25 - Screw connection

3241048

https://www.phoenixcontact.com/us/products/3241048



Cable gland made from brass with metric thread, IP40 protection

WP-GT BRASS M25 - Screw connection

3241034

https://www.phoenixcontact.com/us/products/3241034



Cable gland made from brass with metric thread, rotatable, IP40 protection



1419247

https://www.phoenixcontact.com/us/products/1419247

WP-G BRASS IP65 M25 - Screw connection

3241062

https://www.phoenixcontact.com/us/products/3241062



Cable gland made from brass with metric thread, IP65 protection

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com