

# Han 100A axial module, female 10-25 mm<sup>2</sup>



| Part number        | 09 14 002 2753                          |
|--------------------|---|
| Specification      | Han 100A axial module, female 10-25 mm² |
| HARTING eCatalogue | https://b2b.harting.com/09140022753     |

Image is for illustration purposes only. Please refer to product description.

#### Identification

| Category           | Modules                       |
|--------------------|-------------------------------|
| Series             | Han-Modular <sup>®</sup>      |
| Type of module     | Han <sup>®</sup> 100 A module |
| Size of the module | Double module                 |

#### Version

| Termination method | Axial screw termination |
|--------------------|-------------------------|
| Gender             | Female                  |
| Number of contacts | 2                       |

### Technical characteristics

| Conductor cross-section  | 10 25 mm²           |
|--------------------------|---------------------|
| Rated current            | 100 A               |
| Rated voltage            | 1,000 V             |
| Rated impulse voltage    | 8 kV                |
| Pollution degree         | 3                   |
| Rated voltage acc. to UL | 600 V               |
| Insulation resistance    | >10 <sup>10</sup> Ω |
| Contact resistance       | ≤0.3 mΩ             |
| Stripping length         | 12 14 mm            |
| Tightening torque        | 6 7 Nm              |
| Limiting temperature     | -40 +125 °C         |
|                          |                     |



#### Technical characteristics

Mating cycles ≥500

## Material properties

| Material (insert)                         | Polycarbonate (PC)                                     |
|---|--|
| Colour (insert)                           | RAL 7032 (pebble grey)                                 |
| Material (contacts)                       | Copper alloy   |
| Surface (contacts)                        | Silver plated  |
| Material flammability class acc. to UL 94 | V-0  |
| RoHS                                      | compliant with exemption                               |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                                | compliant with exemption                               |
| China RoHS                                | 50   |
| REACH Annex XVII substances               | Not contained  |
| REACH ANNEX XIV substances                | Not contained  |
| REACH SVHC substances                     | Yes  |
| REACH SVHC substances                     | Lead   |
| ECHA SCIP number                          | 5dbb3851-b94e-4e88-97a1-571845975242                   |
| California Proposition 65 substances      | Yes  |
| California Proposition 65 substances      | Lead<br>Nickel   |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08)                                   |
| Requirement set with Hazard Levels        | R22 (HL 1-3)<br>R23 (HL 1-3)                           |

#### Specifications and approvals

| Specifications | IEC 60664-1<br>IEC 61984   |
|----------------|--|
| UL / CSA       | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076<br>UL 2237 PVVA2.E318390<br>CSA-C22.2 No. 182.3 PVVA8.E318390 |
| Approvals      | DNV GL   |

#### Commercial data

| Packaging size | 1    |
|----------------|------|
| Net weight     | 70 g |

Product data sheet 09 14 002 2753 Han 100A axial module, female 10-25 mm²



#### Commercial data

| Country of origin              | Germany   |
|--------------------------------|---|
| European customs tariff number | 85389099  |
| GTIN                           | 5713140019805   |
| ETIM                           | EC000438  |
| eCl@ss                         | 27440217 Module for industrial connectors (power/signals) |