

USB keyboard INT, TKL-105, Cable with connector type A Desktop keyboard for devices with corresponding interface Color: black Further information, Quantity and content: see technical data



General information	
Product type designation	USB keyboard international US
Control elements	
Version of actuating element	Long-stroke key with 4 mm contact travel
Operating principle of the actuating element	Keyboard with long-stroke keys with membrane switching contacts
Input device	
• Scroll wheel	No
• Movement tracking	none
Keyboard fonts	
• Design	Keyboard with long-stroke keys
• Keyboard assignment	105 keys, international US layout
• Color of the buttons	Black
• Color of the key inscription	White
• Key illumination	No
• Function keys	Yes
— Number of function keys	12
— Number of function keys with LEDs	0
— Programmable	No
• Number pad	Yes; Free-standing
• status LED displays	Yes; Num, Caps and Scroll
— for number pad	Yes
— for Shift keys	Yes
• Multi-key operation	No
— 2-key rollover	No
— n-key rollover	Yes; 10 finger system, quick typing possible
Connection type	
• USB	Yes; USB 2.0 type A
• PS/2	No
• Cable length	0 m; See cable length
Frame size/design	
• Standard	Yes; For industrial applications
Installation type/mounting	
Mounting	Desktop
Mounting type	none
Supply voltage	
Rated value (DC)	5 V; via USB
Battery	
Battery-operated	No; maintenance-free
Interfaces	
Number of USB interfaces	1; USB 2.0

EMC	
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> Limit class B, for use in residential areas 	Yes; Compliance with EN 55032 Class B limit values; interference emission: EN 55016-2-3:2014-11 (30 MHz to 6 GHz) and interference immunity EN 61000-4-2,3,4 passed
Degree and class of protection	
IP (all-round)	IP68 all-round and dishwasher safe
IP (at the front)	USB connector without degree of protection
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; cUL
cULus	Yes; cUL
KC approval	Yes
EAC (formerly Gost-R)	Yes
BIS	No; required for export to India
RoHS conformity	Yes
Suitable for safety functions	No
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	No; possible under certain conditions
Ambient temperature during operation	
<ul style="list-style-type: none"> min. 	0 °C
<ul style="list-style-type: none"> max. 	70 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> min. 	-20 °C
<ul style="list-style-type: none"> max. 	60 °C
Relative humidity	
<ul style="list-style-type: none"> Operation, max. 	80 %; no condensation
<ul style="list-style-type: none"> Condensation permissible 	No
Operating systems	
Runs under operating system	
<ul style="list-style-type: none"> Windows CE 	Yes
<ul style="list-style-type: none"> Windows Vista 	Yes
<ul style="list-style-type: none"> Windows XP 	Yes
<ul style="list-style-type: none"> Windows 7 	Yes
<ul style="list-style-type: none"> Windows 8 	Yes
<ul style="list-style-type: none"> Windows 10 	Yes
Cables	
Cable length	1.5 m; USB
Mechanics/material	
Material	
<ul style="list-style-type: none"> Plastic 	Yes; Black
Enclosure material (front)	
<ul style="list-style-type: none"> Plastic 	Yes; ABS with antimicrobial coating
Enclosure color (front)	Black
Enclosure color (rear)	Black
Torques/forces	
<ul style="list-style-type: none"> Breakdown torque 	0.53 N·m; Switching force buttons
Service life	
<ul style="list-style-type: none"> Number of operating cycles, keys 	10 000 000; Operations (minimum)
Dimensions	
Width	459 mm
Height	35 mm
Depth	174 mm
Weights	
Weight (without packaging)	800 g
Weight (with packaging)	1 620 g
Scope of supply	
Delivery quantity in pieces	1
Other	
printable with laser printer	No

Merchandise	Yes; GETT TKL-105
Manufacturer name	GETT Gerätetechnik GmbH
Manufacturer's address	Mittlerer Ring 1, 08233 Treuen (Vogtland), Germany
contacting the manufacturer	Phone +49 37468 660-0, email: info@gett.de
Target devices	For SIMATIC HMI devices and IPCs with the appropriate slot
Note:	Corresponds to KL24603
Usable in the following products	
• Product 1	6AV2124-*
• Product 2	6AV2125-*
• Product 3	6AV2145-*
• Product 4	6AV7880-*
• Product 5	6AV7863-3MA00-0AA0
• Product 6	6AV7863-3MA00-0SA0
• Product 7	6AV7863-3MA20-0AA0
• Product 8	6AV7863-3TA00-0AA0
• Product 9	6AV7250-*
• Product 10	6AV7251-*
• Product 11	6AV7863*
• Product 12	6AV2128-3*
• Product 13	6AV6642-0BD01-3AX0
• Product 14	6AV6642-0BC01-1AX1
• Product 15	6AV6642-0DC01-1AX0
• Product 16	6AV6642-0DA01-1AX0
• Product 17	6AV6642-0EA01-3AX0
• Product 18	6AV6545-0CC10-0AX0
• Product 19	6AV6545-0AH10-0AX*
• Product 20	6AV6545-0DA10-0AX0
• Product 21	6AV6545-0DB10-0AX0
• Product 22	6AV6644-*
• Product 23	6AV6643-*
• Product 24	6AV2123-2*
• Product 25	6AV7862-2BC*
• Product 26	6AV7862-2BD*
• Product 27	6AV7862-2BE*
• Product 28	6AV7862-2BF*

last modified:

4/21/2021 