XACA042212932011 PENDANT STATION 600VAC 10AMP XAC SPECIAL



Main

Device short name	XAC
Enclosure type	Rainproof enclosure indoor/outdoor Corrosion resistance enclosure indoor/outdoor Dustproof enclosure indoor/outdoor Dust and damp proof enclosure indoor/outdoor
Operator profile	4 projecting push-buttons

Complementary

Line Rated Current	10 A	
Electrical Connection	Screw clamp terminal	
Enclosure material	Yellow polypropylene	
Material	Yellow polypropylene	
Permissible voltage	600 V	

Environment

NEMA Degree of Protection	NEMA 4/4X
14EW/ (Degree of) Toteotion	

Ordering and shipping details

Category	US10CS222473	
Discount Schedule	0CS2	
GTIN	785901161813	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	25.60 oz (725.748 g)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Toxic heavy metal free	Yes	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
Contractual warranty		
Warranty	18 months	