



Main

Net Weight	11.99 oz (340 g)
Product or Component Type	Communication card
Ambient Air Temperature for Storage	-22...122 °F (-30...50 °C)
Ambient air temperature for operation	32...122 °F (0...50 °C)
Communication Port Protocol	Zigbee Pro
Standards	FCC part 15 Subpart C
Storage Relative Humidity	0...95 % non-condensing
Relative Humidity	0...95 %
Range	EcoStruxure Building Expert

Complementary

Accessory / separate part categor	Communication accessory
-----------------------------------	-------------------------

Ordering and shipping details

Category	US1DE1021009
Discount Schedule	DE10
GTIN	3606480772498
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.65 in (4.2 cm)
Package 1 Width	2.95 in (7.5 cm)
Package 1 Length	4.80 in (12.2 cm)
Package 1 Weight	1.09 oz (31 g)

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.