

Part Number: 2128254004

Product Description: DDR4 DIMM Socket, Vertical Surface Mount, 0.76µm Gold Plating, 288 Circuits, with 4.00mm Fork Lock, Black Housing, Black Latch, with Pick-and-Place

Tape

Status: Active

Series Number: 212825

**Product Category:** Memory Module

Connectors

#### **Documents & Resources**

### **Drawings**

<u>Drawing 2128254004\_sd.pdf</u> Packaging Design Drawing PK-78730-001-001.pdf

### 3D Models and Design Files

3D Model 2128254004\_stp.zip

#### **Specifications**

Application Specification AS-78730-001-001.pdf Application Specification AS-78730-002-001.pdf Product Specification PS-78730-001-001.pdf

## **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

# Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

## **Part Details**

## General

Status	Active
Category	Memory Module Connectors
Series	212825
Description	DDR4 DIMM Socket, Vertical Surface Mount, 0.76µm Gold Plating, 288 Circuits, with 4.00mm Fork Lock, Black Housing, Black Latch, with Pick-and-Place Tape
Component Type	Socket
JEDEC Outline	MO-309
Product Family	DDR4 DIMM Sockets
Product Name	DDR4 DIMM
UPC	196823358197

## **Electrical**

Current - Maximum per Contact	0.75A
Voltage - Maximum	29V AC (RMS)/DC

# Physical

Circuits (Loaded)	288
Circuits (maximum)	288
Durability (mating cycles max)	25
Entry Angle	Vertical (Top Entry)
Housing Color	Black
Keying to Mating Part	None
Latch Color	Black
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin

Material - Resin	High Temperature Polyamide
Net Weight	6.500/g
Packaging Type	Tray
PCB Locator	Yes
PCB Retention	Yes
Pitch - Mating Interface	0.85mm
Pitch - Termination Interface	0.85mm
Plating min - Mating	0.760µm
Plating min - Termination	2.540µm
Temperature Range - Operating	-55° to +85°C
Termination Interface Style	Surface Mount

This document was generated on Apr 09, 2024