

LINEAR TECHNOLOGY MATERIALS DECLARATION

1t1469cs8#pbf

(Engineering Calculation)

SOIC

(printed on: 2020-07-11 19:36:41)

TOTAL MASS (g) : 0.076452

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|----------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.004518 | 1000000 | 59096.015625 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000188 | 1000000 | 2459.06420898 | | |
| Lead Frame | A42 | Copper (Cu) | 7440-50-8 | 0.000000 | 0 | 0 | | |
| | | Iron (Fe) | 7439-89-6 | 0.014071 | 580000 | 184050.46875 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000000 | 0 | 0 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000000 | 0 | 0 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.010189 | 420000 | 133273.421875 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.024260 | 1000000 | 317323.90625 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.001477 | 1000000 | 19317.4121094 | | |
| | | External Plating Total: | | | | 0.001477 | 1000000 | 19317.4121094 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.000194 | 1000000 | 2537.54467773 | | |
| Internal Plating Total: | | | | 0.000194 | 1000000 | 2537.54467773 | | |
| Die Attach | ELECTRICALLY CONDUCTIVE ADHESIVE | Silver (Ag) | 7440-22-4 | 0.001210 | 750000 | 15826.9550781 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000403 | 250000 | 5271.29199219 | | |
| Die Attach Total: | | | | 0.001613 | 1000000 | 21098.2441406 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.006603 | 150000 | 86368.0859375 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.036094 | 820000 | 472114.125 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.001100 | 25000 | 14388.140625 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000220 | 5000 | 2877.62817383 | | |
| | | Encapsulation Total: | | | | 0.044017 | 1000000 | 575747.9375 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000185 | 1000000 | 2419.82348633 | | |
| | | | | | TOTAL MASS (g) : | 0.076452 | | |