

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

1t1630is8#pbf

(Engineering Calculation)

SOIC

(printed on: 2020-07-11 19:25:12)

**TOTAL MASS (g) : 0.076307**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.004397	1000000	57622.6171875		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000183	1000000	2398.21191406		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.023653	975000	309972.15625		
		Iron (Fe)	7439-89-6	0.000582	24000	7627.10009766		
		Phosphorus (P)	7723-14-0	0.000007	300	91.7348861694		
		Zinc (Zn)	7440-66-6	0.000017	700	222.784729004		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.024259</b>	<b>1000000</b>	<b>317913.78125</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.001477	1000000	19354.1210938		
		<b>External Plating Total:</b>				<b>0.001477</b>	<b>1000000</b>	<b>19354.1210938</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000194	1000000	2542.36669922		
<b>Internal Plating Total:</b>				<b>0.000194</b>	<b>1000000</b>	<b>2542.36669922</b>		
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.001189	750000	15581.8251953		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000396	250000	5189.57324219		
<b>Die Attach Total:</b>				<b>0.001585</b>	<b>1000000</b>	<b>20771.3984375</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.006604	150000	86545.3125		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.036102	820000	473116.125		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.001101	25000	14428.5869141		
		Carbon Black (C)	1333-86-4	0.000220	5000	2883.09643555		
		<b>Encapsulation Total:</b>				<b>0.044027</b>	<b>1000000</b>	<b>576973.125</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000185	1000000	2424.421875		
					<b>TOTAL MASS (g) :</b>	<b>0.076307</b>		