

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

1t1809is6#trpbf

(Engineering Calculation)

TSOT-23

(printed on: 2020-07-11 20:18:39)

**TOTAL MASS (g) : 0.012533**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.000559	1000000	44603.1171875		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.004582	975000	365601.9375		
		Iron (Fe)	7439-89-6	0.000113	24000	9016.37207031		
		Phosphorus (P)	7723-14-0	0.000001	300	79.7909011841		
		Zinc (Zn)	7440-66-6	0.000003	700	239.37272644		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.004699</b>	<b>1000000</b>	<b>374937.46875</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.000644	1000000	51365.875		
		<b>External Plating Total:</b>				<b>0.000644</b>	<b>1000000</b>	<b>51365.875</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000080	1000000	6383.27246094		
		<b>Internal Plating Total:</b>				<b>0.000080</b>	<b>1000000</b>	<b>6383.27246094</b>
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.000408	750000	32554.6894531		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000136	250000	10851.5625		
<b>Die Attach Total:</b>				<b>0.000544</b>	<b>1000000</b>	<b>43406.25</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.000772	130000	61598.5820312		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.004930	830000	393369.125		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.000208	35000	16596.5078125		
		Carbon Black (C)	1333-86-4	0.000030	5000	2393.72729492		
		<b>Encapsulation Total:</b>				<b>0.005940</b>	<b>1000000</b>	<b>473958</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000067	1000000	5345.99072266		
					<b>TOTAL MASS (g) :</b>	<b>0.012533</b>		