

## Precision, JFET Input Operational Amplifier

### FEATURES

- Low Input Offset Voltage  $V_{IO}=400\mu\text{V}$  max.  
 $V_{IO}=700\mu\text{V}$  max.  
( $T_a = -40^\circ\text{C}$  to  $+125^\circ\text{C}$ )
- Low Input Offset Voltage Drift  $\Delta V_{IO}/\Delta T=5\mu\text{V}/^\circ\text{C}$  max.  
( $T_a = -40^\circ\text{C}$  to  $+125^\circ\text{C}$ )
- Low Supply Current  $I_{CC}=1.3\text{mA}/\text{ch}$  typ.
- High Slew Rate  $SR=20\text{V}/\mu\text{s}$  typ.
- Wide Bandwidth  $f_t=7\text{MHz}$  typ.
- Low Noise  $e_n=10\text{nV}/\sqrt{\text{Hz}}$  typ. (at  $f=1\text{kHz}$ )
- Low Input Bias Current  $I_B=80\text{pA}$  max. (at  $T_a=25^\circ\text{C}$ )
- No Phase Reversal
- RF noise Immunity
- Guaranteed Temperature  $T_{opr} = -40^\circ\text{C}$  to  $+125^\circ\text{C}$
- Operating Voltage  $V_{opr} = \pm 4.5\text{V}$  to  $\pm 16\text{V}$
- Package

NJM8512	MSOP8 (VSP8) meet JEDEC MO-187-DA
NJM8513	SOP8 JEDEC 150 mil SSOP14



### GENERAL DESCRIPTION

The NJM8512/NJM8513 are Dual/Quad high precision JFET input operational amplifier featuring low offset, low offset drift, low bias current, high slew rate, low noise and wide operating temperature range. The precision performance, high speed and low noise make the NJM8512/NJM8513 especially suitable for filter and amplification of high speed and small signal in instruments, automated test equipment, sensors and other precision applications.

### APPLICATIONS

- Current Sensor
- Photodiode Amplification
- Reference Voltage Circuit
- Automatic Test Equipment

### ELECTRICAL CHARACTERISTICS



### PIN CONFIGURATION

Pin Function	<p>(Top View)</p> <p>A OUTPUT 1, A -INPUT 2, A +INPUT 3, V- 4, V+ 8, B OUTPUT 7, B -INPUT 6, B +INPUT 5</p>		<p>(Top View)</p> <p>A OUTPUT 1, A -INPUT 2, A +INPUT 3, V+ 4, B +INPUT 5, B -INPUT 6, B OUTPUT 7, D OUTPUT 14, D -INPUT 13, D +INPUT 12, V- 11, C +INPUT 10, C -INPUT 9, C OUTPUT 8</p>
	Package Outline	MSOP8          SOP8	
PART NUMBER	NJM8512AR NJM8512BR	NJM8512AE NJM8512BE	NJM8513AV NJM8513BV

# NJM8512/NJM8513

## ■ ABSOLUTE MAXIMUM RATINGS (Ta=25°C, unless otherwise noted.)

PARAMETER	SYMBOL	RATING	UNIT
Supply Voltage	$V^+V^-$	±18	V
Differential Input Voltage	$V_{ID}$	±36 (Note1)	V
Input Voltage	$V_{IN}$	$V^- - 0.3$ to $V^+ + 0.3$ (Note2)	V
Input Current	$I_{IN}$	±10(Note3)	mA
Power Dissipation MSOP8 (VSP8) SOP8 SSOP14	$P_D$	(2-layer / 4-layer ) 595(Note4) / 805 (Note4) 690 (Note4) / 1000 (Note4) 490 (Note4) / 630 (Note4)	mW
Output Short-Circuit Duration		Infinite( $T_a = 25^\circ$ ) (Note4)	
Operating Temperature Range	$T_{opr}$	-40 to +125	°C
Junction Temperature	$T_{jmax}$	+150	°C
Storage Temperature Range	$T_{stg}$	-65 to +150	°C

(Note1) Differential Input Voltage is the voltage difference between +INPUT and -INPUT.

(Note2) The normal operation will establish when any input is within the Common Mode Input Voltage Range of electrical characteristics.

(Note3) If the input voltage exceeds the supply voltage, the input current must be limited 10 mA or less by using a restriction resistance.

(Note4) 2-layer : EIA/JEDEC STANDARD Test board (76.2 x 114.3 x 1.6mm, 2layers, FR-4) mounting.

4-layer : EIA/JEDEC STANDARD Test board (76.2 x 114.3 x 1.6mm, 4layers, FR-4) mounting.

See Figure "Fig.1-1 : Power Dissipation Curve" when ambient temperature is over 25°C.

Figure1-A: Power Dissipation Derating Curve





Figure1-B: Power Dissipation Derating Curve



## ■ RECOMMENDED OPERATING VOLTAGE (Ta=25°C)

PARAMETER	SYMBOL	RATING	MIN.	TYP.	MAX.	UNIT
Supply Voltage	$V^+V^-$		±4.5	-	±16	V

# NJM8512/NJM8513

## ■ ELECTRICAL CHARACTERISTICS ( $V^+ / V^- = \pm 15V$ , $T_a = 25^\circ C$ , $V_{ICM} = 0V$ , unless otherwise noted.)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Input Characteristics						
Input Offset Voltage						
NJM8512Bx / NJM8513Bx	$V_{IO1}$		-	80	400	$\mu V$
	$V_{IO2}$	$T_a = -40^\circ C$ to $125^\circ C$	-	-	700	$\mu V$
NJM8512Ax / NJM8513Ax	$V_{IO1}$		-	80	800	$\mu V$
	$V_{IO2}$	$T_a = -40^\circ C$ to $125^\circ C$	-	-	1400	$\mu V$
Input Offset Voltage Drift						
NJM8512Bx / NJM8513Bx	$\Delta V_{IO} / \Delta T$	$T_a = -40^\circ C$ to $125^\circ C$	-	0.8	5	$\mu V / ^\circ C$
	$\Delta V_{IO} / \Delta T$	$T_a = -40^\circ C$ to $125^\circ C$	-	1	9	$\mu V / ^\circ C$
Input Bias Current	$I_{B1}$		-	25	80	pA
	$I_{B2}$	$T_a = -40^\circ C$ to $125^\circ C$	-	-	35	nA
Input Offset Current	$I_{IO1}$		-	6	75	pA
	$I_{IO2}$	$T_a = -40^\circ C$ to $125^\circ C$	-	-	2	nA
Common Mode Input Voltage Range	$V_{ICM1}$	CMR 86dB	-12.5	-	+12.5	V
	$V_{ICM2}$	CMR 80dB, $T_a = -40^\circ C$ to $125^\circ C$	-12.5	-	+12.5	V
Common Mode Rejection Ratio	CMR1	$V_{CM} = -12.5V$ to $+12.5V$	86	108	-	dB
	CMR2	$V_{CM} = -12.5V$ to $+12.5V$ , $T_a = -40^\circ C$ to $125^\circ C$	80	-	-	dB
	CMR3	$V_{CM} = -10V$ to $+10V$	100	120	-	dB
Voltage Gain	$A_{V1}$	$R_L = 2k\Omega$ , $V_O = -13.5V$ to $+13.5V$	90	100	-	dB
	$A_{V2}$	$R_L = 2k\Omega$ , $V_O = -13.5V$ to $+13.5V$ , $T_a = -40^\circ C$ to $125^\circ C$	82	-	-	dB
	$A_{V3}$	$R_L = 10k\Omega$ , $V_O = -13.5V$ to $+13.5V$	98	106	-	dB
Input capacitance	$C_{IN}$		-	10	-	pF
Channel Separation	CS	DC	-	125	-	dB
Output Characteristics						
Maximum Output Voltage	$V_{OH1}$	$R_L = 10k\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	+14.0	+14.2	-	V
	$V_{OL1}$	$R_L = 10k\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	-	-14.9	-14.6	V
	$V_{OH2}$	$R_L = 2k\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	+13.8	+14.1	-	V
	$V_{OL2}$	$R_L = 2k\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	-	-14.8	-14.4	V
	$V_{OH31}$	$R_L = 600\Omega$	+13.5	+13.9	-	V
	$V_{OH32}$	$R_L = 600\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	+11.4	-	-	V
	$V_{OL41}$	$R_L = 600\Omega$	-	-14.3	-13.8	V
	$V_{OL42}$	$R_L = 600\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	-	-	-12.1	V
Supply Characteristics						
Supply Current (ALL Amps) : NJM8512	$I_{CC1}$	$G_V = +1$ , $R_L =$	-	2.6	3.0	mA
	$I_{CC2}$	$G_V = +1$ , $R_L =$ , $T_a = -40^\circ C$ to $125^\circ C$	-	-	3.3	mA
Supply Current (ALL Amps) : NJM8513	$I_{CC1}$	$G_V = +1$ , $R_L =$	-	5.2	6.0	mA
	$I_{CC2}$	$G_V = +1$ , $R_L =$ , $T_a = -40^\circ C$ to $125^\circ C$	-	-	6.6	mA
Supply Voltage Rejection Ratio	SVR1	$V^+ / V^- = \pm 4.5V$ to $\pm 16V$	86	110	-	dB
	SVR2	$V^+ / V^- = \pm 4.5V$ to $\pm 16V$ , $T_a = -40^\circ C$ to $125^\circ C$	80	-	-	dB
Dynamic Performance						
Unity Gain Frequency	fT	$G_V = +100$ , $R_L = 2k\Omega$ , $C_L = 10pF$	-	7	-	MHz
Slew Rate	+SR	RISE, $G_V = +1$ , $V_{IN} = 2V_{pp}$ , $R_L = 2k\Omega$	-	20	-	V/ $\mu s$
	-SR	FALL, $G_V = +1$ , $V_{IN} = 2V_{pp}$ , $R_L = 2k\Omega$	-	20	-	V/ $\mu s$
Settling Time	ts1	To 0.1%, 0V to 10V step, $G_V = +1$	-	0.7	-	$\mu s$
	ts2	To 0.01%, 0V to 10V step, $G_V = +1$	-	1.0	-	$\mu s$
Phase Margin	$\Phi_M$		-	70	-	deg
Total Harmonic Distortion	THD	$f_o = 1kHz$ , $G_V = +1$ , $R_L = 2k\Omega$	-	0.0004	-	%
Noise Performance						
Input Voltage Noise Density	$V_{NI}$	$f_o = 0.1Hz$ to $10Hz$	-	0.9	-	$\mu V_{pp}$
	en1	$f_o = 10Hz$	-	20	-	nV/ Hz
	en2	$f_o = 100Hz$	-	11	-	nV/ Hz
	en3	$f_o = 1kHz$	-	10	-	nV/ Hz
	en4	$f_o = 10kHz$	-	9	-	nV/ Hz

(Note) Measurement is to be conducted in pulse testing.







# NJM8512/NJM8513

## ■ ELECTRICAL CHARACTERISTICS ( $V^+V^- = \pm 5V$ , $T_a = 25^\circ C$ , $V_{ICM} = 0V$ , unless otherwise noted.)







PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Input Characteristics						
Input Offset Voltage						
NJM8512Bx / NJM8513Bx	$V_{IO1}$		-	80	400	$\mu V$
	$V_{IO2}$	$T_a = -40^\circ C$ to $125^\circ C$	-	-	700	$\mu V$
NJM8512Ax / NJM8513Ax	$V_{IO1}$		-	80	800	$\mu V$
	$V_{IO2}$	$T_a = -40^\circ C$ to $125^\circ C$	-	-	1400	$\mu V$
Input Offset Voltage Drift						
NJM8512Bx / NJM8513Bx	$\Delta V_{IO}/\Delta T$	$T_a = -40^\circ C$ to $125^\circ C$	-	0.8	5	$\mu V/^\circ C$
NJM8512Ax / NJM8513Ax	$\Delta V_{IO}/\Delta T$	$T_a = -40^\circ C$ to $125^\circ C$	-	1	9	$\mu V/^\circ C$
Input Bias Current						
	$I_{B1}$		-	21	75	pA
	$I_{B2}$	$T_a = -40^\circ C$ to $125^\circ C$	-	-	31	nA
Input Offset Current						
	$I_{IO1}$		-	5	50	pA
	$I_{IO2}$	$T_a = -40^\circ C$ to $125^\circ C$	-	-	2	nA
Common Mode Input Voltage Range						
	$V_{ICM1}$	CMR 86dB	-2	-	+2.5	V
	$V_{ICM2}$	CMR 80dB, $T_a = -40^\circ C$ to $125^\circ C$	-2	-	+2.5	V
Common Mode Rejection Ratio						
	CMR1	$V_{CM} = -2V$ to $+2.5V$	86	108	-	dB
	CMR2	$V_{CM} = -2V$ to $+2.5V$ , $T_a = -40^\circ C$ to $125^\circ C$	80	-	-	dB
	CMR3	$V_{CM} = -1V$ to $+2V$	92	113	-	dB
Voltage Gain						
	$A_{V1}$	$R_L = 2k\Omega$ , $V_O = -3V$ to $+3V$	85	93	-	dB
	$A_{V2}$	$R_L = 2k\Omega$ , $V_O = -3V$ to $+3V$ , $T_a = -40^\circ C$ to $125^\circ C$	80	-	-	dB
	$A_{V3}$	$R_L = 10k\Omega$ , $V_O = -3V$ to $+3V$	90	100	-	dB
Input capacitance	$C_{IN}$		-	10	-	pF
Channel Separation	CS	DC	-	125	-	dB
Output Characteristics						
Maximum Output Voltage						
	$V_{OH1}$	$R_L = 10k\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	+4.1	+4.3	-	V
	$V_{OL1}$	$R_L = 10k\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	-	-4.9	-4.7	V
	$V_{OH2}$	$R_L = 2k\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	+3.9	+4.2	-	V
	$V_{OL2}$	$R_L = 2k\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	-	-4.9	-4.5	V
	$V_{OH31}$	$R_L = 600\Omega$	+3.7	+4.1	-	V
	$V_{OH32}$	$R_L = 600\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	+3.6	-	-	V
	$V_{OL41}$	$R_L = 600\Omega$	-	-4.8	-4.3	V
	$V_{OL42}$	$R_L = 600\Omega$ , $T_a = -40^\circ C$ to $125^\circ C$	-	-	-4.2	V
Supply Characteristics						
Supply Current (ALL Amps) : NJM8512						
	$I_{CC1}$	$G_V = +1$ , $R_L =$	-	2.0	3.0	mA
	$I_{CC2}$	$G_V = +1$ , $R_L =$ , $T_a = -40^\circ C$ to $125^\circ C$	-	-	3.3	mA
Supply Current (ALL Amps) : NJM8513						
	$I_{CC1}$	$G_V = +1$ , $R_L =$	-	4.0	6.0	mA
	$I_{CC2}$	$G_V = +1$ , $R_L =$ , $T_a = -40^\circ C$ to $125^\circ C$	-	-	6.6	mA
Dynamic Performance						
Unity Gain Frequency	fT	$G_V = +100$ , $R_L = 2k\Omega$ , $C_L = 10pF$	-	7	-	MHz
Slew Rate						
	+SR	RISE, $G_V = +1$ , $V_{IN} = 2V_{pp}$ , $R_L = 2k\Omega$	-	18	-	V/ $\mu s$
	-SR	FALL, $G_V = +1$ , $V_{IN} = 2V_{pp}$ , $R_L = 2k\Omega$	-	18	-	V/ $\mu s$
Settling Time	ts1	To 0.1%, 0V to 4V step, $G_V = +1$	-	0.5	-	$\mu s$
Phase Margin	$\Phi_M$		-	65	-	deg
Total Harmonic Distortion	THD	f <sub>o</sub> =1kHz, $G_V = +1$ , $R_L = 2k\Omega$	-	0.0005	-	%
Noise Performance						
Input Voltage Noise Density						
	$V_{NI}$	f <sub>o</sub> =0.1Hz to 10Hz	-	0.9	-	$\mu V_{pp}$
	en1	f <sub>o</sub> =10Hz	-	20	-	nV/ Hz
	en2	f <sub>o</sub> =100Hz	-	11	-	nV/ Hz
	en3	f <sub>o</sub> =1kHz	-	10	-	nV/ Hz
	en4	f <sub>o</sub> =10kHz	-	9	-	nV/ Hz







(Note) Measurement is to be conducted in pulse testing.

## ELECTRICAL CHARACTERISTICS




# NJM8512/NJM8513






# NJM8512/NJM8513


Maximum Output Voltage vs. Load Resistance




Maximum Output Voltage vs. Load Resistance




Maximum Output Voltage vs. Temperature




Maximum Output Voltage vs. Temperature



Maximum Output Voltage vs. Output Current




Maximum Output Voltage vs. Output Current




**Small-Signal Step Response (Road Capacitance)**

$V^+/V^- = \pm 15V$ ,  $G_v = 0dB$ ,  $V_{IN} = 1V_{pp}$ ,  $R_L = 2k\Omega$ ,  $T_a = 25^\circ C$




**Small-Signal Step Response (Temperature)**

$V^+/V^- = \pm 15V$ ,  $G_v = 0dB$ ,  $V_{IN} = 1V_{pp}$ ,  $R_L = 2k\Omega$ ,  $C_L = 10pF$




**Large Signal Step Response**

$V^+/V^- = \pm 15V$ ,  $G_v = 0dB$ ,  $V_{IN} = 10V_{pp}$ ,  $R_L = 2k\Omega$




**Slew Rate vs. Temperature**

$V^+/V^- = \pm 15V$ ,  $V_{IN} = 2V_{pp}$ ,  $f = 100kHz$ ,  $G_v = 0dB$ ,  $C_L = 10pF$ ,  $R_L = 2k\Omega$




**Slew Rate vs. Temperature**

$V^+/V^- = \pm 5V$ ,  $V_{IN} = 2V_{pp}$ ,  $f = 100kHz$ ,  $G_v = 0dB$ ,  $C_L = 10pF$ ,  $R_L = 2k\Omega$




# NJM8512/NJM8513


**1Hz to 100Hz Input Voltage Noise**  
 $V^*V = \pm 15V$ , 1 to 100Hz BPF




**Input Voltage Noise Density vs. Frequency**  
 $G_v = 40dB$ ,  $R_G = 100\Omega$ ,  $R_L = 10k\Omega$ ,  $T_a = 25^\circ C$




**THD + Noise vs. Output Voltage**  
 $V^*V = \pm 15V$ ,  $A_v = +1$ ,  $R_L = 2k\Omega$ ,  $T_a = 25^\circ C$




**THD + Noise vs. Output Voltage**  
 $V^*V = \pm 5V$ ,  $A_v = +1$ ,  $R_L = 2k\Omega$ ,  $T_a = 25^\circ C$



**Channel Separation vs. Frequency**  
 $V^*V = \pm 15V$ ,  $R_F = 100k\Omega$ ,  $R_S = 1k\Omega$ ,  $T_a = 25^\circ C$ ,  
 $R_L = 2k\Omega$  to  $0V$ ,  $V_o = 5V_{rms}$




**Channel Separation vs. Frequency**  
 $V^*V = \pm 5V$ ,  $R_F = 100k\Omega$ ,  $R_S = 1k\Omega$ ,  $T_a = 25^\circ C$ ,  
 $R_L = 2k\Omega$  to  $0V$ ,  $V_o = 1V_{rms}$




**Short Circuit Output Current**

$V^+/V^- = \pm 15V$ ,  $V_{IN+} = 0V$ ,  $V_O = 0V$ ,  $T_a = 25^\circ C$



**Input Voltage vs. Output Voltage**


$V^+/V^- = \pm 5V$ ,  $A_v = 0dB$ ,  $R_L = 10k\Omega$





## ■PACKAGE DIMENSIONS




### SOP8 JEDEC 150 mil



# NJM8512/NJM8513

## ■PACKAGE DIMENSIONS

### SSOP14



UNIT:mm

[CAUTION]  
The specifications on this data book are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this data book are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.