

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE COMPACT LINE interface module for Siemens S7-1500 systems with S7-1500 specific labeling, with push-in connection, module width: 97.7 mm

## Your advantages

- Single 50-pin FLK header
- Printed channel markings
- Three-level, screw terminal field connections

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 2908496             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | C423                |
| Product key                          | CK2387              |
| Catalog page                         | Page 494 (C-5-2019) |
| GTIN                                 | 4055626357690       |
| Weight per piece (including packing) | 248.4 g             |
| Weight per piece (excluding packing) | 248.4 g             |
| Customs tariff number                | 85366990            |
| Country of origin                    | US                  |

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

## Technical data

### Product properties

|                     |                        |
|---------------------|------------------------|
| Product type        | Interface module       |
| Product family      | VARIOFACE Professional |
| Number of positions | 50                     |
| No. of channels     | 8                      |

### Electrical properties

|                                           |         |
|-------------------------------------------|---------|
| Max. permissible operating voltage        | 25 V AC |
|                                           | 60 V DC |
| Max. current carrying capacity per branch | 1 A     |
| Max. total current of voltage supply      | 7 A     |

### Supported controller SIEMENS S7-1500

|                   |                    |
|-------------------|--------------------|
| Suitable I/O card | 6ES7531-7KF00-0AB0 |
|                   | 6ES7531-7LH00-0AB0 |
|                   | 6ES7531-7MH00-0AB0 |
|                   | 6ES7531-7NF00-0AB0 |
|                   | 6ES7531-7NF10-0AB0 |
|                   | 6ES7531-7PF00-0AB0 |
|                   | 6ES7532-5HF00-0AB0 |
|                   | 6ES7531-7QF00-0AB0 |
|                   | 6ES7550-1AA01-0AB0 |
|                   | 6ES7551-1AB01-0AB0 |
|                   | 6ES7552-1AA00-0AB0 |
|                   | 6ES7553-1AA00-0AB0 |

### Connection data

#### Field level

|                                  |                                              |
|----------------------------------|----------------------------------------------|
| Connection method                | Push-in connection                           |
| Stripping length                 | 8 mm                                         |
| Conductor cross section rigid    | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross section flexible | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross section AWG      | 26 ... 14                                    |

#### Controller level

|                       |                   |
|-----------------------|-------------------|
| Connection method     | IDC/FLK pin strip |
| Number of connections | 1                 |
| Number of positions   | 50                |
| Pitch                 | 2.54 mm           |

### Signaling

|                |    |
|----------------|----|
| Status display | No |
|----------------|----|

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

|                        |    |
|------------------------|----|
| Status display present | No |
|------------------------|----|

## Dimensions

### Item dimensions

|        |         |
|--------|---------|
| Width  | 97.7 mm |
| Height | 75.8 mm |
| Depth  | 63 mm   |

## Material specifications

|                                        |                             |
|----------------------------------------|-----------------------------|
| Color                                  | gray (RAL 7042)             |
| Flammability rating according to UL 94 | V0                          |
| Housing insulation material            | Polyamide PA non-reinforced |

## Environmental and real-life conditions

### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Ambient temperature (operation)         | -20 °C ... 60 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

## Standards and regulations

|                       |              |
|-----------------------|--------------|
| Standards/regulations | IEC 60664    |
|                       | DIN EN 50178 |

## Mounting

|                   |                   |
|-------------------|-------------------|
| Mounting type     | DIN rail mounting |
| Mounting position | any               |

## Notes

|         |                                                                                                                                                                                                                                                                                |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General | For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met. |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|



<https://www.phoenixcontact.com/us/products/2908496>

[illegible]

Technical drawing of the Phoenix Contact 1600000 connector. The drawing includes two views: a side view on the left and a front view on the right. The side view shows the connector's profile with a width dimension of 63. The front view shows the connector's face with a height dimension of 75,8 and a width dimension of 97,7. The front view also displays a grid of 36 positions, labeled L+, M, 2, 4, 6, 8, 10, 12, 14, 16, 22, 24, 26, 28, 30, 32, 34, and 36. The Phoenix Contact logo is visible on the side view.

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2908496>

| CSA<br>Approval ID: 2122203 |                       |                       |                   |                             |
|-----------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                             | 60 V                  | 7 A                   | 26 - 14           | -                           |
| per branch                  | 60 V                  | 1 A                   | 26 - 14           | -                           |

| cUL Recognized<br>Approval ID: FILE E 238705 |                       |                       |                   |                             |
|----------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                              | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                              | 60 V                  | 7 A                   | 26 - 14           | -                           |
| per branch                                   | 60 V                  | 1 A                   | 26 - 14           | -                           |

| UL Recognized<br>Approval ID: FILE E 238705 |                       |                       |                   |                             |
|---------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                             | 60 V                  | 7 A                   | 26 - 14           | -                           |
| per branch                                  | 60 V                  | 1 A                   | 26 - 14           | -                           |

| CSAus<br>Approval ID: 2122203 |                       |                       |                   |                             |
|-------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                               | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                               | 60 V                  | 7 A                   | 26 - 14           | -                           |
| per branch                    | 60 V                  | 1 A                   | 26 - 14           | -                           |

| cULus Recognized |  |  |  |  |
|------------------|--|--|--|--|
|------------------|--|--|--|--|

| cCSAus |  |  |  |  |
|--------|--|--|--|--|
|--------|--|--|--|--|

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141152 |
| ECLASS-13.0 | 27141152 |
| ECLASS-12.0 | 27141152 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002780 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>


## Accessories

### FLK EZ-DR.../.../... - Cable

2295059

<https://www.phoenixcontact.com/us/products/2295059>

Round cable, with preassembly, not shielded, variable cable length



---

### FLK EZ-DR-S.../.../... - Cable

2295046

<https://www.phoenixcontact.com/us/products/2295046>

Round cable, with preassembly, shielded, variable cable length



# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

## UC-TM 4 - Marker for terminal blocks

0818111

<https://www.phoenixcontact.com/us/products/0818111>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 4.2 mm, lettering field size: 3.6 x 10.5 mm, Number of individual labels: 120

---

## UC-TM 6 - Marker for terminal blocks

0818085

<https://www.phoenixcontact.com/us/products/0818085>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

## VIP-3/PT/FLK50/AN/S7-1500 - Passive module

2908496

<https://www.phoenixcontact.com/us/products/2908496>



### UCT-TM 6 - Marker for terminal blocks

0828736

<https://www.phoenixcontact.com/us/products/0828736>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 60

---

### ZB 5,08:UNBEDRUCKT - Zack marker strip

0809793

<https://www.phoenixcontact.com/us/products/0809793>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.08 mm, lettering field size: 4.98 x 10.5 mm, Number of individual labels: 10

## VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

## ZB 22:UNBEDRUCKT - Zack marker strip

0811862

<https://www.phoenixcontact.com/us/products/0811862>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 22 mm, lettering field size: 10.5 x 21.8 mm, Number of individual labels: 4

## FLK 50/EZ-DR/ 50/KONFEK - Cable

2289065

<https://www.phoenixcontact.com/us/products/2289065>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 0.5 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/ 100/KONFEK - Cable

2289078

<https://www.phoenixcontact.com/us/products/2289078>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 1 m

---

## FLK 50/EZ-DR/ 150/KONFEK - Cable

2289081

<https://www.phoenixcontact.com/us/products/2289081>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 1.5 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/ 200/KONFEK - Cable

2289094

<https://www.phoenixcontact.com/us/products/2289094>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 2 m

---

## FLK 50/EZ-DR/ 250/KONFEK - Cable

2289104

<https://www.phoenixcontact.com/us/products/2289104>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 2.5 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/ 300/KONFEK - Cable

2289117

<https://www.phoenixcontact.com/us/products/2289117>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 3 m

---

## FLK 50/EZ-DR/ 350/KONFEK - Cable

2289120

<https://www.phoenixcontact.com/us/products/2289120>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 3.5 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/ 400/KONFEK - Cable

2289133

<https://www.phoenixcontact.com/us/products/2289133>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 4 m

---

## FLK 50/EZ-DR/ 450/KONFEK - Cable

2289573

<https://www.phoenixcontact.com/us/products/2289573>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 4.5 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/ 500/KONFEK - Cable

2289586

<https://www.phoenixcontact.com/us/products/2289586>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 5 m

---

## FLK 50/EZ-DR/ 550/KONFEK - Cable

2289599

<https://www.phoenixcontact.com/us/products/2289599>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 5.5 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/ 600/KONFEK - Cable

2289609

<https://www.phoenixcontact.com/us/products/2289609>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 6 m

---

## FLK 50/EZ-DR/ 700/KONFEK - Cable

2289625

<https://www.phoenixcontact.com/us/products/2289625>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 7 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/ 750/KONFEK - Cable

2289638

<https://www.phoenixcontact.com/us/products/2289638>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 7.5 m

---

## FLK 50/EZ-DR/ 800/KONFEK - Cable

2289641

<https://www.phoenixcontact.com/us/products/2289641>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 8 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/ 850/KONFEK - Cable

2289654

<https://www.phoenixcontact.com/us/products/2289654>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 8.5 m

---

## FLK 50/EZ-DR/ 900/KONFEK - Cable

2289667

<https://www.phoenixcontact.com/us/products/2289667>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 9 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/1000/KONFEK - Cable

2289683

<https://www.phoenixcontact.com/us/products/2289683>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 10 m

---

## FLK 50/EZ-DR/ 125/KONFEK - Cable

2296197

<https://www.phoenixcontact.com/us/products/2296197>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 1.25 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/1200/KONFEK - Cable

2296223

<https://www.phoenixcontact.com/us/products/2296223>



Round cable set; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 12 m

---

## FLK 50/EZ-DR/ 50/KONFEK/S - Cable

2299097

<https://www.phoenixcontact.com/us/products/2299097>



Assembled shielded round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position) (The braided shield is routed to a separate cable end.); cable length: 0.5 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/ 100/KONFEK/S - Cable

2299107

<https://www.phoenixcontact.com/us/products/2299107>



Assembled shielded round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position) (The braided shield is routed to a separate cable end.); cable length: 1 m

---

## FLK 50/EZ-DR/ 150/KONFEK/S - Cable

2299110

<https://www.phoenixcontact.com/us/products/2299110>



Assembled shielded round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position) (The braided shield is routed to a separate cable end.); cable length: 1.5 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/ 200/KONFEK/S - Cable

2299123

<https://www.phoenixcontact.com/us/products/2299123>



Assembled shielded round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position) (The braided shield is routed to a separate cable end.); cable length: 2 m

---

## FLK 50/EZ-DR/ 300/KONFEK/S - Cable

2299136

<https://www.phoenixcontact.com/us/products/2299136>



Assembled shielded round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position) (The braided shield is routed to a separate cable end.); cable length: 3 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/ 400/KONFEK/S - Cable

2299149

<https://www.phoenixcontact.com/us/products/2299149>



Assembled shielded round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position) (The braided shield is routed to a separate cable end.); cable length: 4 m

---

## FLK 50/EZ-DR/ 600/KONFEK/S - Cable

2299152

<https://www.phoenixcontact.com/us/products/2299152>



Assembled shielded round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position) (The braided shield is routed to a separate cable end.); cable length: 6 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

## FLK 50/EZ-DR/1000/KONFEK/S - Cable

2299178

<https://www.phoenixcontact.com/us/products/2299178>



Assembled shielded round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position) (The braided shield is routed to a separate cable end.); cable length: 10 m

---

## CABLE-FLK50/0,14/HF/ 0,5M - Cable

2314134

<https://www.phoenixcontact.com/us/products/2314134>



Assembled, halogen-free round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 0.5 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## CABLE-FLK50/0,14/HF/ 1,0M - Cable

2314147

<https://www.phoenixcontact.com/us/products/2314147>



Assembled, halogen-free round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 1 m

---

## CABLE-FLK50/0,14/HF/ 1,5M - Cable

2314150

<https://www.phoenixcontact.com/us/products/2314150>



Assembled, halogen-free round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 1.5 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## CABLE-FLK50/0,14/HF/ 2,0M - Cable

2314163

<https://www.phoenixcontact.com/us/products/2314163>



Assembled, halogen-free round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 2 m

---

## CABLE-FLK50/0,14/HF/ 2,5M - Cable

2314176

<https://www.phoenixcontact.com/us/products/2314176>



Assembled, halogen-free round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 2.5 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## CABLE-FLK50/0,14/HF/ 3,0M - Cable

2314189

<https://www.phoenixcontact.com/us/products/2314189>



Assembled, halogen-free round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 3 m

---

## CABLE-FLK50/0,14/HF/ 4,0M - Cable

2314192

<https://www.phoenixcontact.com/us/products/2314192>



Assembled, halogen-free round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 4 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module




2908496

<https://www.phoenixcontact.com/us/products/2908496>

## CABLE-FLK50/0,14/HF/ 5,0M - Cable

2314202

<https://www.phoenixcontact.com/us/products/2314202>



Assembled, halogen-free round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 5 m

---

## CABLE-FLK50/0,14/HF/10,0M - Cable

2314244

<https://www.phoenixcontact.com/us/products/2314244>



Assembled, halogen-free round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 10 m

# VIP-3/PT/FLK50/AN/S7-1500 - Passive module



2908496

<https://www.phoenixcontact.com/us/products/2908496>

## CABLE-FLK50-0,14-HF/... - Cable

2314257

<https://www.phoenixcontact.com/us/products/2314257>



Assembled, halogen-free round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: variable

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)