

# CT2244

## Banana Jack Panel Mount

# Datasheet

Press fit 4mm Safety Banana Jack (socket) accepts sheathed or...

### Description

4 mm Safety Banana Jack (socket) accepts sheathed or shrouded banana plugs and meets the latest international safety standard IEC 61010-031 to 1,000 V CAT III and 600 V CAT IV. Fast Push-in assembly in either metal or plastic panels.

Termination is with 0.080" (2mm) solder hole for wire attachment.

- Materials: Body: Polyamide (Nylon); Jack: Brass, Nickel Plt
- Minimum Panel Thickness: Plastic .080" (2mm); Metal .060" (1.5mm)
- Available in 9 colors



*Technical data subject to change.*

© Cal Test Electronics 2018.

[caltestelectronics.com](http://caltestelectronics.com)

**Cal Test**  
ELECTRONICS 

All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of 25°C ± 5°C.

### **Specifications**

<b>IEC Rating</b>	1,000 V CAT III / 600 V CAT IV
<b>Current Max</b>	36 A
<b>Resistance Max</b>	5 milliohms
<b>Temperature (degrees)</b>	-20 to +80C
<b>RoHS (2011/65/EU)</b>	Compliant

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: [caltestelectronics.com](http://caltestelectronics.com)

*Technical data subject to change.*

© Cal Test Electronics 2018.

[caltestelectronics.com](http://caltestelectronics.com)

