

Part Number: 2147612225

Product Description: Pre-Crimped Lead Micro-Fit 3.0 Female-to-Pigtail, Gold (Au) Plating, 450.00mm Length, 18 AWG, Red

Status: Active

Series Number: 214761

**Product Category :** Power and Signal Cable Assemblies

#### **Documents & Resources**

#### **Drawings**

Drawing 2147612225\_sd.pdf

## **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | <b>©</b>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21            |
| REACH SVHC         | Not Contained per D(2023)8585-DC<br>(23 Jan 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

## Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## **EU RoHS Certificate of Compliance**

#### **Part Details**

## General

| Status                 | Active  |
|------------------------|---|
| Category               | Power and Signal Cable Assemblies   |
| Series                 | 214761  |
| Description            | Pre-Crimped Lead Micro-Fit 3.0<br>Female-to-Pigtail, Gold (Au) Plating,<br>450.00mm Length, 18 AWG, Red |
| Application            | Power, Wire-to-Board, Wire-to-Wire  |
| Assembly Configuration | Pre-crimped Lead Only   |
| Connector to Connector | Micro-Fit 3.0 Term-to-Pigtail   |
| Keyword                | Pre-Crimped Leads   |
| Product Family         | Off-the-Shelf Pre-Crimped Leads   |
| Product Name           | Micro-Fit 3.0   |
| UPC                    | 193264574711  |

## Electrical

| Current - Maximum per Contact | 8.5A |
|-------------------------------|------|
|-------------------------------|------|

# Physical

| Cable Length                   | 450.00mm             |
|--------------------------------|----------------------|
| Circuits (Loaded)              | 1                    |
| Circuits (maximum)             | 1                    |
| Color - Resin                  | Red                  |
| Gender                         | Female-Pigtail       |
| Material - Metal               | Phosphor Bronze      |
| Material - Plating Mating      | Gold                 |
| Material - Plating Termination | Tin                  |
| Net Weight                     | 5.021/g              |
| Packaging Type                 | Bag                  |
| Plating min - Mating           | 0.762µm              |
| Plating min - Termination      | 2.540μm              |
| Single Ended                   | Yes                  |
| Termination Interface Style    | Crimp or Compression |
| Wire/Cable Type                | UL 10002             |
| Wire Insulation Diameter       | 1.85mm max.          |

| Wire Size (AWG) | 18 |
|-----------------|----|
|-----------------|----|

## Use with Part(s)

| Description                                     | Part Number  |
|---|--------------|
| Micro-Fit 3.0 Dual Row Receptacle<br>Housings   | 43025        |
| Micro-Fit 3.0 Single Row Receptacle<br>Housings | <u>43645</u> |
| Micro-Fit BMI Dual Row Receptacle<br>Housings   | 44133        |
| Micro-Fit BMI Single Row<br>Receptacle Housings | <u>46623</u> |

This document was generated on Apr 13, 2024