
# **Detailed Specifications & Technical Data**



ENGLISH MEASUREMENT VERSION

# AX102572 Faceplates and Panels - MediaFlex MDVO Style Insert 2-port, Flush







For more Information please call

1-800-Belden1



## **General Description:**

Part Numbers:

Kit of 10 MediaFlex MDVO Module Insert, 2-port, flush, ivory

Capacity         Zonnedors           Max. Capacity         Zonnedors           Front Connection:         Plush           Image: Capacity         Plush           <	Usage (Overall)	
Paysical Characteristics (Connectivity)         2 connectors           Cross         Fund Connections         Fund           Port Connections         Fund         Fund           Dimensions         Fund         Fund	Suitable Applications:	
Conceptor         2 connectors           Fond Connection:         Push           Image: Connection:	Related Parts:	- Compatible with 10GX, CAT6+ and CAT5E MDVO-style Modular Jacks and MDVO Multimedia Modules
Max. Gapacity:         2 connectors:           For Connector::         Fush           Discription::         Fush           Partial::         Fush           Partial::         Fush           Discription::         Fush           Store::         Fush           Store::         Fush           Store::         Fush           Store::         Fush           Store::         Fush           Store::         Fush           Fush         Fush           Store::         Fush           Store::         Fush           Store::         Fush           Store::         Fush	Physical Characteristics (Connectivity)	
Access For Connection: Function Functio	Capacity	
Find Connection:         Fush           Image: Statistic S	Max. Capacity:	2 connectors
Dimensions:         Height (in) Width (in) Depth (in) 0.225 0.050         Dimensions:         Biscription Material:         Dimensions:         Dimension:         Dimensio	Access	
	Front Connection:	Flush
Besiciption Material           Inserts         Resciciption Material           Inserts         Resciciption Material           Color:         vov           Color:         Nov           Verial         Nov           Verial </td <td>Dimensions: Height (in.) Width (in.) Depth (in.)</td> <td></td>	Dimensions: Height (in.) Width (in.) Depth (in.)	
coir:         wory           Weight:         0.120 lbs.           Packaging:         10 iserts packaged in a suitable plastic bag           Packaging:         10 iserts packaged in a suitable plastic bag           Memotional for a suitable plastic bag         10 iserts packaged in a suitable plastic bag           Bornector/Hardware Retention:         20 lbs.           Storage Temperature Range:         40°C To +70°C           Installation Temperature Range:         -10°C To +60°C           Operating Temperature Range:         -10°C To +60°C           Tool Compatibility:         Termination Station (AX101852), Release Tool (AX101185)           Versettibe Specifications and Agency Compliance Oversettibility         Versettibility           Indiver #38 (China RoHS):         Yes           EU Directive 20029/SIEC (RoHS):         Yes           Statigeting:         CA, Bi-national Standard Listed           Statigeting:         Yes           Statigeting:         Yes           Suitability - Indoor:         Yes           Suitab	Materials: Description Material	
Weight:       0.120 lbs.         Packaging       Packaging:         Packaging:       10 inserts packaged in a suitable plastic bag         Mechanical Characteristics (Connectivity)       20 lbs.         Storage Temperature Range:       40°C To +70°C         Installation Temperature Range:       10°C To +60°C         Operating Temperature Range:       10°C To +60°C         To I Compatibility:       Termination Station (AX101852), Release Tool (AX101185)         Applicable Specifications and Agency Compliance (Overall)       Applicable Standards & Environmental Programs         EU Directive 2002/95/EC (RoHS):       Yes         EU RoHS Compliance Date (mm/dytyyy):       07/01/2006         Mil Order #39 (China RoHS):       Yes         Safery Listing:       ACA, Bi-national Standard Listed         Sutability - Indoor:       Yes         Termsmission Characteristics (Connectivity)       Yes         Notes: For proper installation Guide PX102063 available on our web site at http://www.belden.com	Color	
Weight:         0.120 lbs.           Packaging:         10 inserts packaged in a suitable plastic bag           Mechanical Characteristics (Connectivity)         20 lbs.           Connector/Hardware Retention:         20 lbs.           Storage Temperature Range:         40°C To ~70°C           Installation Temperature Range:         -10°C To ~60°C           Operating Temperature Range:         -10°C To ~60°C           Operating Temperature Range:         -10°C To ~60°C           Tool Compatibility:         Termination Station (AX101852), Release Tool (AX101185)           Applicable Specifications and Agency Compliance (Vervall)         Yes           EU Directive 2002/05/EC (RoHS):         Yes           EU Directive 2002/05/EC (RoHS):         Yes           Safety Listing:         ACA, Bi-national Standard Listed           Suitability - Indoor:         Yes           Safety Listing:         Yes           Suitability - Indoor:         Yes           Suitability - Indoor:         Yes           Suitability - Indoor:         Yes           Note:         For proper installation refer to Installation Guide PX102063 wilbel on our web site at http://www.belden.com	Color:	lvory
Packaging       Packaging:       10 Inserts packaged in a suitable plastic bag         Packaging:       10 Inserts packaged in a suitable plastic bag         Mechanical Characteristics (Connectivity)       20 Ibs.         Connector/Hardware Retention:       20 Ibs.         Storage Temperature Range:       40°C To +70°C         Installation Temperature Range:       10°C To +60°C         Operating Temperature Range:       10°C To +60°C         Tool Compatibility:       Termination Station (AX101852), Release Tool (AX101185)         Applicable Specifications and Agency Compliance (Ov=rall)         Applicable Standards & Environmental Programs         EU Directive 2002/95/EC (RoHS):       Yes         Safety Listing:       ACA, Bi-national Standard Listed         Suitability       Suitability         Suitability - Indoor:       Yes         Tera:mission Characteristics (Connectivity)       Yes         Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com	Weight	
Packaging:         10 inserts packaged in a suitable plastic bag           Bornector/Hardware Retention:         20 lbs.           Storage Temperature Range:         40° C To +70° C           Installation Temperature Range:         -10° C To +60° C           Operating Temperature Range:         -10° C To +60° C           Tool Compatibility:         Termination Station (AX101852), Release Tool (AX101185)           Packaged Compatibility:         Termination Station (AX101852), Release Tool (AX101185)           Packaged Standards & Environmental Programs         Yes           EU Directive 2002/95/EC (RoHS):         Yes           Statiget Tool Compatibility:         Yes           Statiget Tool Compatibility:         Yes           Statiget:         Noner #39 (China RoHS):         Yes           Statiget:         Statiget:         Noner #39 (China RoHS):         Yes           Statiget:         Statiget:         Noner #39 (China RoHS):         Yes           Statiget:         Statiget:         Yes         Yes           Statiget:         Yes         Yes         Yes           Statiget:         Yes         Yes         Yes           Statiget:         Yes         Yes         Yes	Weight:	0.120 lbs.
Mechanical Characteristics (Connectivity)       20 lbs.         Connector/Hardware Retention:       20 lbs.         Storage Temperature Range:       -40°C To +70°C         Installation Temperature Range:       -10°C To +60°C         Operating Temperature Range:       -10°C To +60°C         Tool Compatibility:       Termination Station (AX101852), Release Tool (AX101185)         Applicable Specifications and Agency Compliance (Overall)       Applicable Standards & Environmental Programs         EU Directive 2002/95/EC (RoHS):       Yes         EU RoHS Compliance Date (mm/dd/yyyy):       07/01/2006         Mil Order #39 (China RoHS):       Yes         Safety Listing:       ACA, Bi-national Standard Listed         Suitability       Suitability - Indoor:       Yes         Transmission Characteristics (Connectivity)       Yes         Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com       Prove Particular Particula		
Connector/Hardware Retention:       20 lbs.         Storage Temperature Range:       -40°C To +70°C         Installation Temperature Range:       -10°C To +60°C         Operating Temperature Range:       -10°C To +60°C         Tool Compatibility:       Termination Station (AX101852), Release Tool (AX101185)         Applicable Specifications and Agency Compliance (Overall)         Applicable Standards & Environmental Programs         EU Directive 2002/95/EC (RoHS):       Yes         EU RoHS Compliance Date (mm/dd/yyyy):       07/01/2006         Mil Order #39 (China RoHS):       Yes         Safety Listing:       ACA, Bi-national Standard Listed         Suitability       yes         Suitability       Yes         Notes: For proper installation Guide PX102063 avallable on our web site at http://www.belden.com	Packaging:	10 inserts packaged in a suitable plastic bag
Storage Temperature Range:       -40°C To +70°C         Installation Temperature Range:       -10°C To +60°C         Operating Temperature Range:       -10°C To +60°C         Tool Compatibility:       Termination Station (AX101852), Release Tool (AX101185)         Applicable Specifications and Agency Compliance (Overall)         Applicable Standards & Environmental Programs         EU Directive 2002/95/EC (RoHS):       Yes         EU RoHS Compliance Date (mm/dd/yyyy):       07/01/2006         Mil Order #39 (China RoHS):       Yes         Safety Listing:       ACA, Bi-national Standard Listed         Suitability       yes         Suitability - Indoor:       Yes         Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com	Mechanical Characteristics (Connectivity)	
Installation Temperature Range:       -10°C To +60°C         Operating Temperature Range:       -10°C To +60°C         Tool Compatibility:       Termination Station (AX101852), Release Tool (AX101185)         Applicable Specifications and Agency Compliance (Overall)         Applicable Standards & Environmental Programs         EU Directive 2002/96/EC (RoHS):       Yes         EU RoHS Compliance Date (mm/dd/yyyy):       07/01/2006         Mil Order #39 (China RoHS):       Yes         Safety Listing:       ACA, Bi-national Standard Listed         Suitability       Yes         Suitability       Yes         Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com	Connector/Hardware Retention:	20 lbs.
Operating Temperature Range:       -10°C To +60°C         Tool Compatibility:       Termination Station (AX101852), Release Tool (AX101185)         Applicable Specifications and Agency Compliance (Overall)         Applicable Standards & Environmental Programs         EU Directive 2002/95/EC (RoHS):       Yes         EU RoHS Compliance Date (mm/dd/yyyy):       07/01/2006         Mil Order #39 (China RoHS):       Yes         safety Listing:       ACA, Bi-national Standard Listed         Suitability       Yes         Suitability       Yes         Notes: (Overall)       Yes         Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com	Storage Temperature Range:	-40°C To +70°C
Tool Compatibility:       Termination Station (AX101852), Release Tool (AX101185)         Applicable Specifications and Agency Compliance (Overall)         Applicable Standards & Environmental Programs         EU Directive 2002/95/EC (RoHS):       Yes         EU RoHS Compliance Date (mm/dd/yyyy):       07/01/2006         MII Order #39 (China RoHS):       Yes         Safety Listing:       ACA, Bi-national Standard Listed         Suitability       Yes         Suitability       Yes         Notes: Coverall)       Yes         Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com	Installation Temperature Range:	-10°C To +60°C
Applicable Specifications and Agency Compliance (Overall)         Applicable Standards & Environmental Programs         EU Directive 2002/95/EC (RoHS):       Yes         EU RoHS Compliance Date (mm/dd/yyyy):       07/01/2006         MII Order #39 (China RoHS):       Yes         Safety Listing:       ACA, Bi-national Standard Listed         Suitability       Yes         Suitability       Yes         Transmission Characteristics (Connectivity)       Yes         Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com	Operating Temperature Range:	-10°C To +60°C
Applicable Standards & Environmental Programs         EU Directive 2002/95/EC (RoHS):       Yes         EU RoHS Compliance Date (mm/dd/yyyy):       07/01/2006         MII Order #39 (China RoHS):       Yes         Safety Listing:       ACA, Bi-national Standard Listed         Suitability       Yes         Suitability       Yes         Suitability       Yes         Notes: For proper installation refer to Installation Guide PX102063 ur web site at http://www.belden.com	Tool Compatibility:	Termination Station (AX101852), Release Tool (AX101185)
EU RoHS Compliance Date (mm/dd/yyyy):       07/01/2006         MII Order #39 (China RoHS):       Yes         Safety Listing:       ACA, Bi-national Standard Listed         Suitability       Suitability         Suitability       Yes         Suitability       Yes         Suitability       Yes         Suitability       Yes         Notes: For proper installation refer to Installation Guide PX102063 are bit at http://www.belden.com		ance (Overall)
MII Order #39 (China RoHS):       Yes         Safety Listing:       ACA, Bi-national Standard Listed         Suitability       Yes         Suitability       Yes         Transmission Characteristics (Connectivity)       Yes         Notes: (Overall)       Notes: For proper installation refer to Installation Guide PX102063 aviable on our web site at http://www.belden.com	EU Directive 2002/95/EC (RoHS):	Yes
Safety Listing:       ACA, Bi-national Standard Listed         Suitability       Yes         Transmission Characteristics (Connectivity)       Yes         Notes: (Overall)       Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com	EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
Suitability       Yes         Suitability - Indoor:       Yes         Transmission Characteristics (Connectivity)         Notes (Overall)         Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com	MII Order #39 (China RoHS):	Yes
Suitability - Indoor:     Yes       Transmission Characteristics (Connectivity)       Notes (Overall)       Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com	Safety Listing:	ACA, Bi-national Standard Listed
Notes (Overall) Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com		Yes
Notes (Overall) Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com	Transmission Characteristics (Connectivity)	
Notes: For proper installation refer to Installation Guide PX102063 available on our web site at http://www.belden.com		
		K102063 available on our web site at http://www.belden.com
		·



#### ENGLISH MEASUREMENT VERSION

## AX102572 Faceplates and Panels - MediaFlex MDVO Style Insert 2-port, Flush

Item Number	Color
AX101749	Gray
AX101750	Almond
AX101751	Elec. White
AX101752	Black
AX102612	White
AX102572	lvory

#### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX102572	1 EA	0.120 LB			KIT MFLEX MDVO INSERTS (10/PK)

Revision Number: 0 Revision Date: 08-08-2012

© 2016 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU ROHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is designed only as general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. product.