

2 Port USB VGA Cable KVM Switch - USB Powered with Remote Switch

Product ID: SV211USB



The SV211USB 2-Port VGA Cable KVM Switch lets you control two VGA, USB-equipped PCs with a single monitor, keyboard and mouse.

To help organize your desk without sacrificing valuable work space, this VGA USB KVM switch features a compact footprint and integrated KVM cables that can be connected directly to your systems. Plus, the KVM is USB-powered, eliminating the need for a bulky external power adapter and wall outlet.

This VGA KVM switch offers support for resolutions up to 2048x1536, for the ability to drive a high-resolution VGA display. For simple switching between connected systems, the KVM features a convenient push-button remote switch on a 1.5 meter (5ft) cable, as well as keyboard hot-key support and PC or Mac compatible switching software.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Great for PC test/burn-in computer control, saving the desk space required for two monitors, keyboards and mice

- Perfect for sharing computers and attached peripherals in the home or home office
- Dual system control for single user workstations, increasing user productivity in the office

Features

- Supports resolutions up to 2048x1536
- Switch PCs via push-button, hot-keys or switching software (included)
- Space-saving design, minimal footprint
- Integrated KVM cables and remote switch
- Switching software supports PC and Mac platforms
- USB Powered - No external power adapter required
- Supports hot-plugging
- Remote switch on 1.5m (5ft.) cable

Hardware

Warranty	2 Years
Audio	No
KVM Ports	2
PC Interface	USB
PC Video Type	VGA
Number of Monitors Supported	1
Rack-Mountable	No
Cables Included	Yes
Daisy-Chain	No

Performance

On-Screen Display	No
IP Control	No
Hot-Key Selection	Yes

	Port Selection Support	Push Button, Hotkeys, and Software
<hr/>		
Connector(s)		
	Console Interface(s)	1 - VGA (15 pin, High Density D-Sub) 2 - USB 2.0 Type-A (4 pin, 480Mbps)
	Host Connectors	1 - VGA (15 pin, High Density D-Sub) 1 - USB 2.0 Type-A (4 pin, 480Mbps)
<hr/>		
Software		
	OS Compatibility	Windows 2000, XP, Vista, 7, 8, 8.1, 10, 11 Windows Server 2003, 2008 R2, 2012, 2016, 2019, 2022 Mac OS 10.x (Tested up to 10.9), 9.x
<hr/>		
Special Notes / Requirements		
	Note	OS Compatibility refers to KVM software only - the KVM itself can be used without software on any platform
<hr/>		
Indicators		
	LED Indicators	1 - PC Selection indictor
<hr/>		
Power		
	Power Source	USB-Powered
	Input Voltage	5V DC
	Output Voltage	5 DC
<hr/>		
Environmental		
	Operating Temperature	0C to 40C (32F to 104F)
	Storage Temperature	-20C to 60C (4F to 140F)
	Humidity	0~90% RH Non-Condensing
<hr/>		
Physical Characteristics		
	Color	Black
	Material	Plastic
	Cable Length	33.5 in [850 mm]

Product Length	3.5 in [88 mm]
Product Width	2.6 in [6.6 cm]
Product Height	0.9 in [2.3 cm]
Weight of Product	11.3 oz [321 g]

Packaging Information

Package Quantity	1
Package Length	9.6 in [24.4 cm]
Package Width	6.4 in [16.2 cm]
Package Height	2.4 in [6.0 cm]
Shipping (Package) Weight	15.3 oz [434.0 g]

What's in the Box

Included in Package	1 - KVM Switch
	1 - Software CD
	1 - Instruction Manual

****Product appearance and specifications are subject to change without notice.***