

4 Port USB DisplayPort KVM Switch with Audio

Product ID: SV431DPUA



The SV431DPUA 4 Port USB DisplayPort KVM Switch with Audio combines next generation display standards with seamless KVM control of up to 4 connected PC or Mac computers.

Featuring DisplayPort resolutions of 2560x1600 @60Hz, as well as offering both 7.1 HD digital audio (with supporting displays and sources) and separate 3.5mm stereo audio support. An integrated USB 2.0 hub allows you to share 2 additional peripherals among attached computers as if they were directly connected.

Suitable for high quality static imaging applications such as health care (MRI, X-ray diagnostics, etc.), a maximum resolution of 3840x2400 is supported at reduced refresh rates.

A simple yet comprehensive solution, the 4-port KVM features both front-panel push-button and hotkey switching, and offers a small form factor with rear connection ports, to minimize workspace disruptions.

This product is TAA compliant and backed by a Startech.com 3-year warranty with free lifetime technical support.

If you'd like to mount this KVM switch to your server rack, StarTech.com offers a 1U Rackmount Bracket (sold separately) that turns this KVM into a rackmountable KVM.

Certifications, Reports and Compatibility

















Applications

- Dual system control for a single workstation increasing productivity in the office
- High resolution medical imaging and Health care display, such as MRI and X-Ray display
- Perfect for high-res Digital Signage server control, simplifying access to multiple systems
- Multimedia design, multimedia post-production and video editing
- Great for PC test/burn-in computer control saving the desk space required for multiple monitors, keyboards and mice
- Leverage DisplayPort's high resolution capabilities for Satellite Topography equipment

Features

- 7.1 Channel High Definition Audio support plus dual channel Analog Stereo and Microphone
- Full plug-and-play support with USB keyboards, mice, and connected peripherals
- Hotkey and push-button switching
- Native DisplayPort resolution of 2560x1600 @60Hz; beyond 1080p
- OS independent No driver or software required
- Supports a maximum resolution of 3840x2400 at lower refresh rates
- Supports DDC2B for monitor detection
- Supports hot-plug, un-plug and link status-failure detection
- Integrated 2 port USB 2.0 hub
- User-defined scan time intervals
- VESA and CEA compliant
- Fully compatible with Mini-DisplayPort, HDMI, and DVI adapters

| Hardware | | | |
|----------|--------------|---------|--|
| | Warranty | 3 Years | |
| | Audio | Yes | |
| | KVM Ports | 4 | |
| | PC Interface | USB | |



PC Video Type DisplayPort

Number of Monitors

Supported

1

Rack-Mountable Optional

Cables Included No

Daisy-Chain No

Performance

On-Screen Display No

DVI Support No

IP Control No

Hot-Key Selection Yes

Maximum Digital Resolutions

2560 x 1600 @ 60Hz

Wide Screen Supported Yes

Maximum Number of

Users

1

Port Selection Support Push Button and Hotkeys

MTBF 136000 hours

Connector(s)

Console Interface(s) 2 - 3.5 mm Mini-Jack (3 Position)

1 - DisplayPort (20 pin)

4 - USB 2.0 Type-A (4 pin, 480Mbps)

Host Connectors 8 - 3.5 mm Mini-Jack (3 Position)

4 - DisplayPort (20 pin)

4 - USB B (4 pin)

Software

OS Compatibility OS independent; No software or drivers required

Indicators





LED Indicators 1 - Power

4 - Green - Online indicator (One LED per port)

4 - Red - Select indicator (One LED per port)

Power

Power Source AC Adapter Included

Input Voltage 100 - 240 AC

Input Current 0.8A

Output Voltage 12V DC

Output Current 1.5A

Center Tip Polarity Positive

Plug Type M

Power Consumption (In

Watts)

Environmental

Operating Temperature 0C to 40C (32F to 104F)

18

Storage Temperature -20C to 60C (-4F to 140F)

Humidity 0~80% RH

Physical Characteristics

Color Black

Material Steel

Product Width 8.7 in [22.1 cm]

Product Height 1.7 in [4.4 cm]

Product Depth 5.1 in [130.6 mm]

Weight of Product 2.3 lb [1.0 kg]

Packaging Information

Package Quantity 1



Package Length 16.1 in [41.0 cm]

Package Width 8.3 in [21.2 cm]

Package Height 3.5 in [8.8 cm]

Shipping (Package)

Weight

3.5 lb [1.6 kg]

What's in the Box

Included in Package 1 - 4-port DisplayPort KVM switch

4 - foot pads

1 - universal power adapter (NA/UK/EU/AU)

1 - instruction manual

^{*}Product appearance and specifications are subject to change without notice.