

Specification Sheet

Part Number: 594-53789

EDP paper has a smooth surface, allowing for the highest resolution and print contrast

Repositionable adhesive bonds to a wide variety of substrates and removes without damage

Printable Temporary Signs are sheet fed for easy loading and fast printing

Remove entire backing for max adhesion, or just the thin backing strips for faster sign removal later



Printable Temporary Signs, Removable, 8.5" x 11", EDP Paper, White, 25/pkg

|                |            |
|----------------|------------|
| Article Number | 594-53789  |
| Type           | FASIGNS    |
| Color          | White (WH) |
| Quantity Per   | pack       |

|                      |  |
|----------------------|--|
| Product Description  | <p>Our Printable Temporary Sign is a semi-permanent, repositionable and removable paper label. Each page is 8.5" x 11" and can be printed using any laser or ink jet printer. Print one sign to a page or two 8.5" x 5.5" signs utilizing the built-in microperf. Adhesive will not damage sensitive surfaces like wallpaper, paint, glass, woodwork or drywall. Printable Temporary Signs can be used to create ANSI-compliant signage on demand. Download free templates from the HellermannTyton website to create Danger, Warning, Caution, Notice and Safety signs as needed for construction jobs or other applications requiring fast signage. The backing is split so the entire page of adhesive can be exposed or a narrow strip along the top and bottom can be removed to partially attach sign, making it easier to remove later. HellermannTyton Printable Temporary Signs are rated for 90 days of outdoor use.</p> |
| Short Description    | Printable Temporary Signs, Removable, 8.5" x 11", EDP Paper, White, 25/pkg   |
| Global Part Name     | FASIGNS-EDP-WH   |
| Width W (Imperial)   | 8.5  |
| Width W (Metric)     | 215.9  |
| Thickness T (Metric) | 64.0   |
| Height H (Imperial)  | 11.0   |
| Height H (Metric)    | 279.4  |
| Material             | Type EDP, Paper (EDP)  |
| Material Shortcut    | EDP  |

|                                |                                   |
|--------------------------------|-----------------------------------|
| Adhesive                       | Acrylic                           |
| Halogen Free                   | No                                |
| UV Resistant (Yes/No)          | No                                |
| Adhesive Operating Temperature | -20°F to +250°F (-28°C to +121°C) |
| Operating Temperature          | -20°F to +250°F (-28°C to +121°C) |
| Reach Compliant (Article 33)   | Yes                               |
| ROHS Compliant                 | Yes                               |
| Package Quantity (Imperial)    | 1                                 |
| Package Quantity (Metric)      | 25                                |
| Customs Number                 | 3919905060                        |
| Labels per Column              | 1                                 |
| Labels per Row                 | 1                                 |

### About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)