

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



LED machine light, 24 V DC, emission angle (vertical/Horizontal): 75 °/95 °, length: 790 mm, diameter: 70 mm, degree of protection: IP67, can be swiveled, resistant to coolants and lubricants

Product description

This LED machine light is designed to provide illumination inside or on machinery. You can use the light in harsh environments. This is possible thanks to the following properties: - High type of protection - Resistance to common cooling agents and lubricants - Resistance to vibrations and shock - 4 mm-thick safety glass The 70 mm diameter enables easy replacement of conventional tube lights. Mounting is by means of holders or brackets (neither of which are supplied as standard) in which the light can swivel and the lighting can therefore be optimally aligned.

Your advantages

- Easy mechanical replacement of traditional tube lights (retrofit), thanks to 70 mm diameter
- Plug-in supply line enables free choice of the cable length as well as quick and easy installation
- Focused illumination, thanks to swivel action
- IP67 protection and resistance to cooling agents and lubricants enables use in machine tools
- Can be used at high temperatures and can be subjected to strong vibrations and shocks
- Safety glass enables use even in environments with potential mechanical strain
- ETL approval permits use on the North American market
- Particularly economical thanks to energy-efficient LED technology and an LED service life of at least 60,000 h

Commercial data

Item number	2702488
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR08
Product key	DRL222
Catalog page	Page 507 (C-6-2019)
GTIN	4055626216782
Weight per piece (including packing)	3,030 g
Weight per piece (excluding packing)	2,500 g
Customs tariff number	94054239
Country of origin	DE

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

Technical data

Notes

Order information:	The PLD M-ME MC/D70 mounting holder (Item No. 2702493) or the PLD M-ME MB/D70 mounting bracket (Item No. 2702494) is required in order to mount the light.
--------------------	--

Product properties

Product type	Machine light
Application	Machine tool
Mounting position	any
Special properties	can be swiveled with mounting accessories resistant to coolants and lubricants

Electrical properties

Supply: Module electronics

Connection method	M12 connector (A-coded)
Number of positions	4
Permissible conductor cross section	min. 0.34 mm ²
Supply voltage	24 V DC
Supply voltage range	18 V DC ... 30 V DC
Current consumption	typ. 1.25 A (at 24 V DC)
Power consumption	approx. 30 W (at 24 V DC)
Protective circuit	Surge protection; Varistor and suppressor diode, 36 V DC Reverse polarity protection; Polarity protection diode

Connection data

Connection method	M12 connector (A-coded)
-------------------	-------------------------

Signaling

Light properties

Source of light type	LED
Number of LEDs	60
Color temperature	5000 K ±8 %
Color rendering index	85
Luminous flux	approx. 2300 lm (Net luminous flux)
Luminous efficacy	approx. 77 lm/W
Illumination	max. 1056 lx (Distance of 1 m) min. 518 lx (Distance of 1 m over 1 m ² area)
Average illumination	814 lx (Distance of 1 m over 1 m ² area)
Emission angle	75 ° (C0-C180) 95 ° (C90-C270)
Ordinance	Delegated Regulation (EU) 2019/2015

PLD M 260 W-75/95 790/D70 - LED machine light




2702488

<https://www.phoenixcontact.com/us/products/2702488>

Energy efficiency class	D (1 light source)
	E (1 light source)
Note	This product contains an energy efficiency class D light source.
	This product contains an energy efficiency class E light source.

Dimensions

Dimensional drawing	
Width	70 mm
Height	58 mm
Length	790 mm
Diameter	70 mm
Note on dimensions	Length without M12 flush-type connector

Material specifications

Color	aluminum color
Material ()	Anodized aluminum (Light housing)
	Single-pane safety glass (ESG, thermally toughened float glass) (Pane)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	0 °C ... 45 °C
Degree of protection	IP67
Air pressure (operation)	69 kPa ... 102 kPa
Air pressure (storage/transport)	69 kPa ... 102 kPa
Ambient temperature (storage/transport)	-20 °C ... 75 °C
Permissible humidity (operation)	95 % (non-condensing)
Permissible humidity (storage/transport)	95 % (non-condensing)

Standards and regulations

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Mounting

Mounting type	Screw mounting
Assembly note	Mounting with mounting holders or mounting brackets, please observe the notes in the package slip.
Mounting position	any

PLD M 260 W-75/95 790/D70 - LED machine light


2702488

<https://www.phoenixcontact.com/us/products/2702488>



Drawings

Dimensional drawing



PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2702488>



ETLus

Approval ID: LV-Lighting-Systems



cETL

Approval ID: Luminaires



EAC

Approval ID: TR_TS_D_12879-22

cETLus

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

Classifications

ECLASS

ECLASS-11.0	27110345
ECLASS-12.0	27110345
ECLASS-13.0	27110345

ETIM

ETIM 9.0	EC000348
----------	----------

UNSPSC

UNSPSC 21.0	32151500
-------------	----------

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(a)-I, 6(c), 7(a)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	a3571f2d-7235-4cd3-81b4-6e2dcf0b27c5

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

Mandatory accessories

PLD M-ME MC/D70 - Mounting holder

2702493

<https://www.phoenixcontact.com/us/products/2702493>



Mounting holder, for machine lights PLD M 260 .../D70, Swiveling range $\pm 30^\circ$

PLD M-ME MB/D70 - Mounting bracket

2702494

<https://www.phoenixcontact.com/us/products/2702494>



Mounting bracket, for machine lights PLD M 260 .../D70, Swiveling range $\pm 65^\circ$

Accessories

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

SAC-4P- 1,5-PUR/M12FS - Sensor/actuator cable

1668108

<https://www.phoenixcontact.com/us/products/1668108>



Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, coding: A, cable length: 1.5 m

SAC-4P- 3,0-PUR/M12FS - Sensor/actuator cable

1668111

<https://www.phoenixcontact.com/us/products/1668111>



Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, coding: A, cable length: 3 m

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

SAC-4P- 5,0-PUR/M12FS - Sensor/actuator cable

1668124

<https://www.phoenixcontact.com/us/products/1668124>



Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, coding: A, cable length: 5 m

SAC-4P- 1,5-PUR/M12FR - Sensor/actuator cable

1668221

<https://www.phoenixcontact.com/us/products/1668221>



Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket angled M12, coding: A, cable length: 1.5 m

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

SAC-4P- 3,0-PUR/M12FR - Sensor/actuator cable

1668234

<https://www.phoenixcontact.com/us/products/1668234>



Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket angled M12, coding: A, cable length: 3 m

SAC-4P- 5,0-PUR/M12FR - Sensor/actuator cable

1668247

<https://www.phoenixcontact.com/us/products/1668247>



Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket angled M12, coding: A, cable length: 5 m

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com