

SPORT-2X2-S1

~10° spot beam.

SPECIFICATION:

Dimensions	50.0 x 50.0 mm
Height	16 mm
Fastening	screw
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish	Length
SPORT-2X2-S1	Multi-lens	PMMA	clear		50.0



ORDERING INFORMATION:


Component	Qty in box	MOQ	MPQ	Box weight (kg)
C17991_SPORT-2X2-S1 » Box size: 480 x 280 x 300 mm	512	128	32	10.8



OPTICAL RESULTS (MEASURED):





LED XP-G4
 FWHM / FWTM 9.0° / 20.0°
 Efficiency 96 %
 Peak intensity 24.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED LUXEON HL2X
 FWHM / FWTM 10.0° / 21.0°
 Efficiency 94 %
 Peak intensity 20.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:





Protective plate, glass

Light distribution files



LED LUXEON HL2X
 FWHM / FWTM 10.0° / 21.0°
 Efficiency 97 %
 Peak intensity 21.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):




LED LUXEON HL2X
 FWHM / FWTM 10.0° / 21.0°
 Efficiency 97 %
 Peak intensity 21.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files





LED OSCONIQ C 3030
 FWHM / FWTM 9.0° / 19.0°
 Efficiency 96 %
 Peak intensity 23.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED OSLON Square CSSRM2/CSSRM3
 FWHM / FWTM 9.0° / 18.0°
 Efficiency 97 %
 Peak intensity 27.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):



LED PassivePAQ-R-274x51-NI0-21K-857-5
 FWHM / FWTM 15.0° / 27.0°
 Efficiency 96 %
 Peak intensity 10.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED J Series 5050 Round LES
 FWHM / FWTM 16.0° / 32.0°
 Efficiency 95 %
 Peak intensity 8.6 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED J Series 5050 Round LES
 FWHM / FWTM 16.0° / 32.0°
 Efficiency 87 %
 Peak intensity 7.8 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:




Protective plate, glass

Light distribution files



LED J Series 5050B 6V K Class
 FWHM / FWTM 16.0° / 34.0°
 Efficiency 95 %
 Peak intensity 7.6 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files


OPTICAL RESULTS (SIMULATED):



LED J Series 5050B 6V K Class
 FWHM / FWTM 18.0° / 34.0°
 Efficiency 87 %
 Peak intensity 6.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Protective plate, glass

Light distribution files



LED J Series 5050C 6V E Class
 FWHM / FWTM 16.0° / 32.0°
 Efficiency 96 %
 Peak intensity 8.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Light distribution files



LED XD16
 FWHM / FWTM 8.0° / 16.0°
 Efficiency 87 %
 Peak intensity 28.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Protective plate, glass

Light distribution files




OPTICAL RESULTS (SIMULATED):



LED XHP35.2 HD
FWHM / FWTM 18.0° / 34.0°
Efficiency 86 %
Peak intensity 6.9 cd/Im
LEDs/each optic 1
Light colour/type White
Required components:


Protective plate, glass

Light distribution files



LED XHP35.2 HD
FWHM / FWTM 16.0° / 34.0°
Efficiency 95 %
Peak intensity 7.5 cd/Im
LEDs/each optic 1
Light colour/type White
Required components:


Light distribution files



LED XHP35.2 HI
FWHM / FWTM 14.0° / 28.0°
Efficiency 87 %
Peak intensity 10.6 cd/Im
LEDs/each optic 1
Light colour/type White
Required components:

Protective plate, glass


Light distribution files



OPTICAL RESULTS (SIMULATED):




LED XHP35.2 HI
FWHM / FWTM 14.0° / 26.0°
Efficiency 95 %
Peak intensity 11.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED XHP50.3 HI
FWHM / FWTM 14.0° / 28.0°
Efficiency 95 %
Peak intensity 10.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED XHP50.3 HI
FWHM / FWTM 14.0° / 28.0°
Efficiency 87 %
Peak intensity 9.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Protective plate, glass

Light distribution files


OPTICAL RESULTS (SIMULATED):



LED XM-L3
 FWHM / FWTM 12.0° / 28.0°
 Efficiency 87 %
 Peak intensity 11 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:


Protective plate, glass

Light distribution files




LED XM-L3
 FWHM / FWTM 12.0° / 26.0°
 Efficiency 95 %
 Peak intensity 12.5 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files



LED XP-E
 FWHM / FWTM 6.0° / 14.0°
 Efficiency 95 %
 Peak intensity 52.2 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files




OPTICAL RESULTS (SIMULATED):



LED XP-G2
FWHM / FWTM 10.0° / 20.0°
Efficiency 90 %
Peak intensity 21.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Protective plate, glass


Light distribution files



LED XP-G2 HE
FWHM / FWTM 10.0° / 20.0°
Efficiency 91 %
Peak intensity 23.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:


Protective plate, glass

Light distribution files



LED XP-G2 HE
FWHM / FWTM 8.0° / 18.0°
Efficiency 95 %
Peak intensity 28.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Light distribution files




OPTICAL RESULTS (SIMULATED):



LED XP-G3
 FWHM / FWTM 10.0° / 22.0°
 Efficiency 86 %
 Peak intensity 16.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Protective plate, glass

Light distribution files




LED XP-G3
 FWHM / FWTM 10.0° / 22.0°
 Efficiency 95 %
 Peak intensity 18.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files



LED XP-G4 HI
 FWHM / FWTM 8.0° / 18.0°
 Efficiency 95 %
 Peak intensity 29.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files




OPTICAL RESULTS (SIMULATED):



LED XP-G4 HI
 FWHM / FWTM 8.0° / 18.0°
 Efficiency 87 %
 Peak intensity 23.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Protective plate, glass


Light distribution files



LED XP-L HD
 FWHM / FWTM 12.0° / 26.0°
 Efficiency 90 %
 Peak intensity 12.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Protective plate, glass

Light distribution files



LED XP-L HD
 FWHM / FWTM 12.0° / 26.0°
 Efficiency 95 %
 Peak intensity 13.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files




OPTICAL RESULTS (SIMULATED):



LED XP-L HI
 FWHM / FWTM 10.0° / 20.0°
 Efficiency 87 %
 Peak intensity 22.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Protective plate, glass

Light distribution files




LED XP-L HI
 FWHM / FWTM 8.0° / 18.0°
 Efficiency 96 %
 Peak intensity 26.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files



LED XP-L2
 FWHM / FWTM 14.0° / 28.0°
 Efficiency 95 %
 Peak intensity 10.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files




OPTICAL RESULTS (SIMULATED):



LED XP-L2
 FWHM / FWTM 14.0° / 28.0°
 Efficiency 86 %
 Peak intensity 9.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Protective plate, glass

Light distribution files



LED XP-P
 FWHM / FWTM 6.0° / 14.0°
 Efficiency 95 %
 Peak intensity 52.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Light distribution files



LED XP-P
 FWHM / FWTM 8.0° / 14.0°
 Efficiency 86 %
 Peak intensity 39.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Protective plate, glass

Light distribution files




OPTICAL RESULTS (SIMULATED):



LED LUXEON 3030 2D (Round LES)
 FWHM / FWTM 8.0° / 18.0°
 Efficiency 90 %
 Peak intensity 27.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Protective plate, glass

Light distribution files




LED LUXEON 5050 HE
 FWHM / FWTM 16.0° / 32.0°
 Efficiency 95 %
 Peak intensity 8.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files



LED LUXEON 5050 Round LES
 FWHM / FWTM 18.0° / 34.0°
 Efficiency 95 %
 Peak intensity 7.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files




OPTICAL RESULTS (SIMULATED):



LED LUXEON 5050 Round LES
 FWHM / FWTM 18.0° / 34.0°
 Efficiency 87 %
 Peak intensity 6.6 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:


Protective plate, glass

Light distribution files



LED LUXEON 5050 Square LES
 FWHM / FWTM 20.0° / 36.0°
 Efficiency 95 %
 Peak intensity 6.2 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:


Light distribution files



LED LUXEON 5050 Square LES
 FWHM / FWTM 20.0° / 36.0°
 Efficiency 90 %
 Peak intensity 5.8 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:

Protective plate, glass


Light distribution files



OPTICAL RESULTS (SIMULATED):




LED LUXEON 7070
 FWHM / FWTM 22.0° / 48.0°
 Efficiency 93 %
 Peak intensity 3.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED LUXEON HL2X
 FWHM / FWTM 10.0° / 22.0°
 Efficiency 87 %
 Peak intensity 18.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Protective plate, glass

Light distribution files



LED LUXEON HL2X
 FWHM / FWTM 10.0° / 22.0°
 Efficiency 95 %
 Peak intensity 21 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED LUXEON HL2X-D
 FWHM / FWTM 12.0° / 26.0°
 Efficiency 96 %
 Peak intensity 15.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED LUXEON HL2X-D
 FWHM / FWTM 12.0° / 26.0°
 Efficiency 88 %
 Peak intensity 13.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Protective plate, glass

Light distribution files



LED LUXEON HL2X-P
 FWHM / FWTM 12.0° / 26.0°
 Efficiency 95 %
 Peak intensity 15.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED LUXEON HL2Z
 FWHM / FWTM 8.0° / 18.0°
 Efficiency 95 %
 Peak intensity 27.9 cd/m
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED LUXEON XR-HL2X (L2H2-xxxxxxxMLU010)
 FWHM / FWTM 12.0° / 24.0°
 Efficiency 96 %
 Peak intensity 16.3 cd/m
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED LUXEON XR-HL2X (L2H2-xxxxxxxMLU010)
 FWHM / FWTM 12.0° / 24.0°
 Efficiency 88 %
 Peak intensity 14.1 cd/m
 LEDs/each optic 1
 Light colour/type White
 Required components:




Protective plate, glass

Light distribution files

OPTICAL RESULTS (SIMULATED):




LED SFT-40-WCS
 FWHM / FWTM 8.0° / 18.0°
 Efficiency 95 %
 Peak intensity 30.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED SFT-70X-WCS
 FWHM / FWTM 10.0° / 22.0°
 Efficiency 96 %
 Peak intensity 18.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED SST-20
 FWHM / FWTM 8.0° / 16.0°
 Efficiency 89 %
 Peak intensity 30.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Protective plate, glass

Light distribution files


OPTICAL RESULTS (SIMULATED):



LED SST-70X-WCS
 FWHM / FWTM 16.0° / 30.0°
 Efficiency 87 %
 Peak intensity 8.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Protective plate, glass

Light distribution files




LED SST-70X-WCS
 FWHM / FWTM 16.0° / 30.0°
 Efficiency 96 %
 Peak intensity 8.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files



LED NFMW48xA
 FWHM / FWTM 18.0° / 34.0°
 Efficiency 95 %
 Peak intensity 7.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files




OPTICAL RESULTS (SIMULATED):



LED NV4WB35AM
 FWHM / FWTM 14.0° / 26.0°
 Efficiency 87 %
 Peak intensity 10.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Protective plate, glass

Light distribution files



LED NV4WB35AM
 FWHM / FWTM 14.0° / 26.0°
 Efficiency 96 %
 Peak intensity 11.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Light distribution files



LED NVSW219D
 FWHM / FWTM 10.0° / 22.0°
 Efficiency 90 %
 Peak intensity 19.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Protective plate, glass

Light distribution files




OPTICAL RESULTS (SIMULATED):



LED NVSW219F
FWHM / FWTM 10.0° / 22.0°
Efficiency 95 %
Peak intensity 19.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:


Protective plate, glass

Light distribution files



LED NVSW219F
FWHM / FWTM 10.0° / 22.0°
Efficiency 95 %
Peak intensity 20.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:


Light distribution files



LED NVSW219F
FWHM / FWTM 10.0° / 22.0°
Efficiency 90 %
Peak intensity 17.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Protective plate, glass


Light distribution files



OPTICAL RESULTS (SIMULATED):




LED NVSW519A
 FWHM / FWTM 12.0° / 27.0°
 Efficiency 94 %
 Peak intensity 13.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED NVSxE21A
 FWHM / FWTM 8.0° / 18.0°
 Efficiency 88 %
 Peak intensity 27.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

Protective plate, glass



LED DURIS E 5050 (GW J9LHS1.4M)
 FWHM / FWTM 14.0° / 32.0°
 Efficiency 95 %
 Peak intensity 9.5 cd/lm
 LEDs/each optic 1
 Light colour/type RGBW
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors


LED Duris S5 (2 chip)
FWHM / FWTM 8.0° / 18.0°
Efficiency 95 %
Peak intensity 27.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

OSRAM
Opto Semiconductors


LED Duris S5 (Single chip)
FWHM / FWTM 6.0° / 14.0°
Efficiency 95 %
Peak intensity 45.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

OSRAM
Opto Semiconductors

LED Duris S8
FWHM / FWTM 22.0° / 40.0°
Efficiency 87 %
Peak intensity 4.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Protective plate, glass

Light distribution files

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors


LED Duris S8
FWHM / FWTM 20.0° / 38.0°
Efficiency 95 %
Peak intensity 5.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

OSRAM
Opto Semiconductors

LED OSCONIQ C 3030
FWHM / FWTM 10.0° / 20.0°
Efficiency 87 %
Peak intensity 20.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

Protective plate, glass

OSRAM
Opto Semiconductors

LED OSCONIQ C 3030
FWHM / FWTM 10.0° / 20.0°
Efficiency 96 %
Peak intensity 24.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files


OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED OSCONIQ P 3737 (2W version)
FWHM / FWTM 8.0° / 18.0°
Efficiency 90 %
Peak intensity 26.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Protective plate, glass

Light distribution files




OSRAM
Opto Semiconductors

LED OSCONIQ P 3737 (3W version)
FWHM / FWTM 12.0° / 24.0°
Efficiency 87 %
Peak intensity 14.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Protective plate, glass


Light distribution files



OSRAM
Opto Semiconductors

LED OSCONIQ P 3737 (3W version)
FWHM / FWTM 12.0° / 24.0°
Efficiency 96 %
Peak intensity 15.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:


Light distribution files



OPTICAL RESULTS (SIMULATED):




LED	OSLON Optimal (GF CSSRML.24)
FWHM / FWTM	6.0° / 14.0°
Efficiency	92 %
Peak intensity	41.9 cd/lm
LEDs/each optic	1
Light colour/type	Far Red
Required components:	



Light distribution files



LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	10.0° / 20.0°
Efficiency	86 %
Peak intensity	19.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Light distribution files

Protective plate, glass



LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	8.0° / 18.0°
Efficiency	95 %
Peak intensity	28.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files


OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED LH351B
 FWHM / FWTM 10.0° / 22.0°
 Efficiency 87 %
 Peak intensity 19.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Protective plate, glass


Light distribution files



SAMSUNG

LED LH351B
 FWHM / FWTM 10.0° / 20.0°
 Efficiency 96 %
 Peak intensity 22.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files




SAMSUNG

LED LH351C
 FWHM / FWTM 10.0° / 22.0°
 Efficiency 88 %
 Peak intensity 16.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Protective plate, glass


Light distribution files



OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED	LH351C
FWHM / FWTM	10.0° / 22.0°
Efficiency	96 %
Peak intensity	18.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

SAMSUNG


LED	LH351D
FWHM / FWTM	14.0° / 28.0°
Efficiency	95 %
Peak intensity	11.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

SAMSUNG

LED	LH351D
FWHM / FWTM	14.0° / 28.0°
Efficiency	90 %
Peak intensity	10.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Protective plate, glass

Light distribution files


OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED LH502C
 FWHM / FWTM 18.0° / 35.0°
 Efficiency 90 %
 Peak intensity 6.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Protective plate, glass


Light distribution files



SAMSUNG

LED LH502C
 FWHM / FWTM 18.0° / 36.0°
 Efficiency 95 %
 Peak intensity 6.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:


Light distribution files




LED Z5M4
 FWHM / FWTM 10.0° / 22.0°
 Efficiency 90 %
 Peak intensity 18 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Protective plate, glass

Light distribution files



OPTICAL RESULTS (SIMULATED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)