

### **TINA-M**

~30° medium beam optimized for Osram Golden Dragon+. Assembly with holder and installation tape.

### **SPECIFICATION:**

Dimensions	Ø 16.1 mm
Height	10.1 mm
Fastening	tape
ROHS compliant	yes 🕕



### **MATERIALS**:


» Box size:

Component	Туре	Material	Colour	Finish	Length
TINA-O-PLUS-M	Single lens	PMMA	clear		16.0
TINA-O-PLUS-H-TAPE-WHT	Holder	PC	white		16.0
TINA-TAPE3	Tape	Acrylic foam	black		16.0

### **ORDERING INFORMATION:**

Component	Qty in box	MOQ	MPQ	Box weight (kg)
FA10643_TINA-M	2016	288	144	4.0

### PRODUCT DATASHEET FA10643\_TINA-M



See also our general installation guide: <a href="www.ledil.com/installation\_guide">www.ledil.com/installation\_guide</a>



### **OPTICAL RESULTS (MEASURED):**

### OSRAM Opto Semiconductors

Opto Semiconductors

LED Golden Dragon+
FWHM / FWTM 30.0° / 58.0°
Efficiency 92 %
Peak intensity 3.2 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

Light distribution files




### **OPTICAL RESULTS (SIMULATED):**



LED XP-L HI
FWHM / FWTM 29.0° / 58.0°
Efficiency 88 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:




Light distribution files



LED LUXEON 5050 Square LES

FWHM / FWTM 35.0° / 76.0°
Efficiency 82 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:



Light distribution files



LED SFT-12R-WES
FWHM / FWTM 28.0° / 55.0°
Efficiency 88 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:




### **OPTICAL RESULTS (SIMULATED):**

### OSRAM Opto Semiconductors

LED OSLON Boost HX (KW CULPM1.TG)

FWHM / FWTM 28.0° / 57.0°
Efficiency 87 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1
Light colour/type White


Required components:




Light distribution files

#### OSRAM Opto Semiconductors

LED SFH 4715AS
FWHM / FWTM 28.0° / 58.0°
Efficiency 87 %
LEDs/each optic 1
Light colour/type IR
Required components:





Light distribution files



# PRODUCT DATASHEET FA10643\_TINA-M

### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

## Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405, Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

## Local sales and technical support

www.ledil.com/ where\_to\_buy

### **Shipping locations**

Poznan, Poland Hong Kong, China

### **Distribution Partners**

www.ledil.com/ where\_to\_buy