

Main

Range	Acti9
Device short name	MSC 18
Product or Component Type	Chassis
Device Application	Distribution

Complementary

Range compatibility	Acti 9 Acti9 IsoBar B distribution board
Line Rated Current	250 A
Short-circuit withstand	25 kA 0.1 s
[I _{cw}] rated short-time withstand current	25 kA
Number of ways	1 way incomer) - 3P 42 outgoer)
Outgoer Pole capacity	42 x 0.71 in (18 mm)
Length	14.96 in (380 mm)
Width	8.46 in (215 mm)


Ordering and shipping details

Category	US10DE200908
Discount Schedule	0DE2
GTIN	9321243001113
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.53 in (24.2 cm)
Package 1 Width	3.70 in (9.4 cm)
Package 1 Length	26.97 in (68.5 cm)
Package 1 Weight	7.32 lb(US) (3.32 kg)

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
China RoHS Regulation	 China RoHS Declaration
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------