



Powering Business Worldwide

Eaton Internal Replacement Battery Cartridge (RBC) for Select 5kVA to 6kVA Online UPS Systems and EBMs

MODEL NUMBER: 744-A1974



UPS backup battery cartridge replaces the expired or aging internal battery in your Eaton UPS system or EBM.

Features

UPS Replacement Battery Cartridge for Select Eaton Double Conversion UPS Systems

This UPS backup battery replacement is compatible with Eaton's SU5000RT, SU5000RTMB, SU5000RTF, SU5000RTFMB, SU6000RT, SU6000RTMB, SU6000RTF, SU6000RTFMB, 9PX5K, 9PX5KP1, 9PX5KP2, 9PX5KTF5, 9PX6K, 9PX6KUS, 9PX6K-10, 9PX6KP1, 9PX6KP2, 9PX6KTF5, 9PX3K3UN, 9PX3K3UNP1, 9PX3K3UNP2 and 9PX3K3UNTF5 UPS systems and BP180RT, 9PXEBM180RT, 9PXEBM180RTUS and 9PXEBM360SP extended battery modules (EBM). Eaton UPS batteries have an expected lifespan of three to five years, so you should take proactive steps to avoid a dead battery and ensure continuous uptime.

Comes Pre-Wired for Quick, Easy Installation

The sealed lead acid (SLA) 744-A1974 internal battery cartridge is hot-swappable, allowing you to install it without powering down any connected equipment. Built to function in a wide range of operating temperatures, the 744-A1974 has been carefully screened and certified to restore your UPS system's runtime performance to its original specifications. It is leakproof, requires no maintenance and comes pre-wired for quick and easy installation in your UPS system.

Specifications

OVERVIEW	
UPC Code	037332282125
INPUT	
Input Phase	Single-Phase
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)

Highlights

- Replacement battery backup for select Eaton 5kVA–6kVA 9PX and SmartOnline UPS and EBMs
- Carefully screened and certified to restore UPS runtime to original specs
- Leakproof internal battery cartridge requires no regular maintenance
- Ships ready for immediate UPS installation to prevent downtime

System Requirements

Compatible only with Eaton's SU5000RT, SU5000RTMB, SU5000RTF, SU5000RTFMB, SU6000RT, SU6000RTMB, SU6000RTF, SU6000RTFMB, 9PX5K, 9PX5KP1, 9PX5KP2, 9PX5KTF5, 9PX6K, 9PX6KUS, 9PX6K-10, 9PX6KP1, 9PX6KP2, 9PX6KTF5, 9PX3K3UN, 9PX3K3UNP1, 9PX3K3UNP2 and 9PX3K3UNTF5 UPS systems and BP180RT, 9PXEBM180RT, 9PXEBM180RTUS and 9PXEBM360SP EBMs

Package Includes

744-A1974 Internal Replacement Battery Cartridge



Powering Business Worldwide

Battery Replacement Description	Hot-swappable, user replaceable batteries. Re-use existing wiring harness.
Hot Swap Battery	Yes
PHYSICAL	
Unit Dimensions (hwd / in.)	11.900 x 14.400 x 25.400
Unit Weight (lbs.)	63.93
Unit Weight (kg)	29.00
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
APPLICATIONS	
Used With	SU5000RT, SU5000RTMB, SU5000RTF, SU5000RTFMB, SU6000RT, SU6000RTMB, SU6000RTF, SU6000RTFMB, 9PX3K3UN, 9PX5K, 9PX6K, 9PXEBM180RT, 9PXEBM180RTUS, 9PXEBM360SP, 9PX6KUS, 9PX3K3UNP1, 9PX3K3UNP2, 9PX3K3UNTF5, 9PX5KP1, 9PX5KP2, 9PX5KTF5, 9PX6K-10, 9PX6KP1, 9PX6KP2, 9PX6KTF5
STANDARDS & COMPLIANCE	
Product Certifications	UL Listed; cUL Listed
Product Compliance	FCC (USA); CE (Europe)

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.