## HMIDT65XFH

EXtreme touchscreen panel, Harmony GTUX, 12 W Display full coated





## Main

Range of Product	Harmony GTUX
Product or Component Type	EXtreme touchscreen panel
Terminal type	Touchscreen display
[Us] rated supply voltage	12 V DC power supply
Supply voltage limits	10.828.8 V
Power consumption in W	12.5 W
Inrush current	30 A

## Complementary

Touchscreen resolution	1024 x 1024	
Pixel resolution	1280 x 800	
Display size	12.1 inch	
Aspect ratio	4:3	
Display type	Colour TFT LCD	
Display resolution	1280 x 800 pixels WVGA	
Display colour	262144 colors	
Luminance	92.90 fc (1000 cd/m²)	
Touch panel	Single touch analogue resistive	
Type of cooling	Natural convection	
Cut-out dimensions	295 (+ 1/- 0) x 217 (+ 1/- 0) mm	
Width	12.15 in (308.5 mm)	
Height	9.07 in (230.5 mm)	
Depth	2.68 in (68 mm)	
Net Weight	7.05 lb(US) (3.2 kg)	

## **Environment**

IP degree of protection	IP66f
	IP67f
	Front panel Type 4X
Standards	UL 61010
	UL 121201
	CSA C22.2 No 213
	CSA C22.2 No 61010-1
	IEC 61132-2
Product Certifications	KC[RETURN]CE[RETURN]RCM[RETURN]EAC[RETURN]ATEX zone
	2/22[RETURN]IEC-
	Ex[RETURN]UL[RETURN]CSA[RETURN]UKCA[RETURN]UKEX
Ambient air temperature for operation	-22158 °F (-3070 °C) IEC 61131-2
Ambient air temperature for storage	-22158 °F (-3070 °C)
Pollution degree	2
Environmental characteristic	3C3
	UV resistant
Relative Humidity	1090 % non-condensing
Operating altitude	6561.68 ft (2000 m)

Vibration resistance	7 mm constant amplitude 59 Hz) IEC 61131-2 19.6 m/s² 9150 Hz) IEC 61131-2
Shock resistance	392 m/s²IEC 61131-2
Electromagnetic compatibility	Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2
Ordering and shipping details	
Category	US10MC222567
Discount Schedule	0MC2
GTIN	3606481572936
Returnability	Yes
Country of origin	US
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.72 in (19.6 cm)
Package 1 Width	17.13 in (43.5 cm)
Package 1 Length	13.19 in (33.5 cm)
Package 1 Weight	6.28 lb(US) (2.85 kg)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEN RoHS  Declaration
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

WEEE