



48 x 48mm

Features :

- True RMS measurement
- 3 Digit 7 segment dual line display
- Direct 30A measurement with built-in CT

Display specifications

Display parameters	Voltage & Current
Type	7 segment
Display	3 digit LED display with dual rows
Colour	Red and Green
Display height	8.6mm
Resolution	Voltage : 1V Current : 0.1A

Input specifications

Rated input voltage	230V AC ($\pm 20\%$)
Rated input current	0.1 to 10A
Operating frequency	50Hz ($\pm 5\%$)
Power consumption	Max 15VA @ 230V AC
Current overload	12A

Accuracy

Voltage	($\pm 1\%$) full scale
Current	($\pm 1\%$) full scale

Environmental specification



Temperature	Operating : -10°C to 55°C Storage : -25 to 70°C
Humidity	95% non-condensing
Pollution degree	II

Mechanical specification

Mounting	Panel
Dimension	48 x 48mm
IP Front	IP 51
IP Back	IP 20
Torque	0.5 N-m

Packaging

Packing material	Corrugated box
Weight	Packed : 120gms Unpacked : 84gms

Dimensions (All are in mm)**Terminal connection****Ordering information**

Product code	Supply voltage	Certification
MVA591-30A-230V	230VAC, $\pm 10\%$ 50 / 60Hz	---