


**Specification**



- Lever body  
Plastic **KT**  
Nylon thermoplastic  
- Glass fiber reinforced  
- With molded-in stainless steel inlay  
- Temperature resistant up to 230 °F (110 °C)
- Color
  - Black, RAL 9005, textured finish **● SW**
  - Orange, RAL 2004, textured finish **● OS**
  - Gray, RAL 7035, textured finish **● GS**
- Threaded stud / retaining screw  
Steel  
- Blackened finish  
- Tensile strength class 5.8
- RoHS compliant

**Information**

Made in the USA, WN 300 adjustable levers are the result of modern industrial design: glass fiber reinforced thermoplastic with molded-in stainless steel inlay.

All such levers have proven to be ideal wherever parts have to be clamped in a confined space or in a particular lever position. The insert is connected to the lever via serrations that can easily be disengaged.

Pulling the lever upwards disengages the serrations, allowing it to be swiveled to the ideal clamping position. When releasing the lever, the serrations automatically re-engage.

see also...

- Adjustable Levers WN 300 (Nylon Plastic, Tapped or Plain Bore Type)
- Adjustable Levers GN 300 (Zinc Die-Cast, Threaded Stud Type)
- Adjustable Levers WN 303 (Nylon Plastic, with Push Button, Threaded Stud Type)
- Adjustable Levers GN 303 (Zinc Die-Cast, with Push Button, Threaded Stud Type)

**On request**

- Special colors, stud lengths, and threads

<p>How to order (Inch)</p> <p style="text-align: center;"> <span style="border: 1px solid red; padding: 2px;">1</span> <span style="border: 1px solid red; padding: 2px;">2</span> <span style="border: 1px solid red; padding: 2px;">3</span> <span style="border: 1px solid red; padding: 2px;">4</span> <span style="border: 1px solid red; padding: 2px;">5</span> </p> <p style="text-align: center; font-weight: bold;">WN 300-KT-30-1/4X20-20-GS</p>	<b>1</b> Material
	<b>2</b> Lever length l <sub>1</sub>
	<b>3</b> Thread d <sub>1</sub>
	<b>4</b> Thread length l <sub>2</sub>
	<b>5</b> Color

<p>How to order (Metric)</p> <p style="text-align: center;"> <span style="border: 1px solid red; padding: 2px;">1</span> <span style="border: 1px solid red; padding: 2px;">2</span> <span style="border: 1px solid red; padding: 2px;">3</span> <span style="border: 1px solid red; padding: 2px;">4</span> <span style="border: 1px solid red; padding: 2px;">5</span> </p> <p style="text-align: center; font-weight: bold;">WN 300-KT-63-M10-80-OS</p>	<b>1</b> Material
	<b>2</b> Lever length l <sub>1</sub>
	<b>3</b> Thread d <sub>1</sub>
	<b>4</b> Thread length l <sub>2</sub>
	<b>5</b> Color

**Inch table**

Dimensions in: inches - millimeters

I <sub>1</sub>	d <sub>1</sub> Thread	I <sub>2</sub>										d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> Stroke
		.39	.47	.63	.79	.98	1.26	-	-	-	-						
1.18 30	10 x 32	10	12	16	20	25	32	-	-	-	-	10	14.5	24.5	4	30.5	.14
1.18 30	10 x 24	12	16	20	25	32	-	-	-	-	-	10	14.5	24.5	4	30.5	.14
1.18 30	1/4 x 20	10	12	16	20	25	32	1.26	1.57	1.77	-	10	14.5	24.5	4	30.5	.14
1.77 45	10 x 32	10	12	16	20	25	32	-	-	-	-	10	14.5	24.5	4	35	.14
1.77 45	10 x 24	12	16	20	25	32	-	-	-	-	-	10	14.5	24.5	4	35	.14
1.77 45	1/4 x 20	10	12	16	20	25	32	1.26	1.57	1.77	-	10	14.5	24.5	4	35	.14
2.48 63	1/4 x 20	12	16	20	25	-	-	-	-	-	-	13.5	19.4	31	6.5	45	.16
2.48 63	5/16 x 18	12	16	20	25	32	40	45	50	63	2.48	13.5	19.4	31	6.5	45	.16
2.48 63	3/8 x 16	16	20	25	32	40	45	50	63	-	-	13.5	19.4	31	6.5	45	.16
3.07 78	3/8 x 16	16	20	25	32	40	45	50	63	2.48	-	16	22.2	36	8	55	.16
3.07 78	1/2 x 13	16	20	25	32	40	45	50	-	-	-	16	22.2	36	8	55	.16
3.62 92	3/8 x 16	16	20	25	32	40	45	50	63	2.48	-	19	25.2	43	11	65	.16
3.62 92	1/2 x 13	16	20	25	32	35	40	45	50	63	2.48	19	25.2	43	11	65	.16

**Metric table**

Dimensions in: millimeters - inches

I <sub>1</sub>	d <sub>1</sub> Thread	I <sub>2</sub>										d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> Stroke
		6	8	10	12	16	-	-	-	-	-						
30 1.18	M 3	-	6 .24	8 .31	10 .39	12 .47	16 .63	-	-	-	-	10	14.5	24.5	4	30.5	.14
30 1.18	M 4	-	10 .39	12 .47	16 .63	20 .79	25 .98	32 1.26	-	-	-	10	14.5	24.5	4	30.5	.14
30 1.18	M 5	-	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	-	-	10	14.5	24.5	4	30.5	.14
30 1.18	M 6	-	10 .39	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	45 1.77	50 1.97	10	14.5	24.5	4	30.5	.14
45 1.77	M 4	-	10 .39	12 .47	16 .63	20 .79	25 .98	32 1.26	-	-	-	10	14.5	24.5	4	35	.14
45 1.77	M 5	-	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	-	-	10	14.5	24.5	4	35	.14
45 1.77	M 6	-	10 .39	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	45 1.77	50 1.97	10	14.5	24.5	4	35	.14
63 2.48	M 6	-	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	-	13.5	19.4	31	6.5	45	.16
63 2.48	M 8	-	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	45 1.77	50 1.97	63 2.48	13.5	19.4	31	6.5	45	.16
63 2.48	M 10	-	16 .63	20 .79	25 .98	32 1.26	40 1.57	45 1.77	50 1.97	63 2.48	80 3.15	13.5	19.4	31	6.5	45	.16
78 3.07	M 8	M 10	16 .63	20 .79	25 .98	32 1.26	40 1.57	45 1.77	50 1.97	63 2.48	80 3.15	16	22.2	36	8	55	.16
78 3.07	M 12	-	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	-	-	-	16	22.2	36	8	55	.16
92 3.62	M 10	M 12	16 .63	20 .79	25 .98	32 1.26	40 1.57	45 1.77	50 1.97	63 2.48	80 3.15	19	25.2	43	11	65	.16