




LF30-CL-M5:15-ZS

Ruland Flat Adjustable Lever, Lever Length 30mm, Stud Thread M5, Stud Length 14mm, Sleeve Length 15mm, Zinc Lever, Stainless Steel Inserts





Description

Ruland LF30-CL-M5:15-ZS is an adjustable clamping lever with a 30mm long flat handle, M5 threaded stud, 14mm stud length, 15mm sleeve, and 35mm overall height. The threaded stud is designed to replace standard M5x15 hardware in Ruland one- and two-piece shaft collars. Once installed on the shaft collar, the lever is turned until the user reaches their desired torque. It does not require any tools to install, making it ideal for applications that require frequent setup changes and adjustments. LF30-CL-M5:15-ZS is black to seamlessly integrate with the aesthetics of most equipment. It is manufactured by Otto Ganter, stocked by Ruland, and RoHS3 and REACH compliant.

Product Specifications

i roduct opcomoduom	,		
Thread (TH)	M5	Stud Length LS	14 mm
Lever Length L1	30 mm	Overall Height H1	35 mm
Hub Height H2	33 mm	Hub Diameter DH	13 mm
Thread Pitch	0.8 mm	Sleeve Length L2	15 mm
Sleeve Diameter D1	8.7 mm	Handle Material	Zinc
Handle Color	Black	Insert and Screw Material	303 Stainless Steel
Weight (lbs)	0.070500	Manufacturer	JW Winco/ Otto Ganter
UPC	634529238417	Country of Origin	Germany
Tariff Code	8487.90.0080	UNSPC	31162807
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Prop 65	▲WARNING This product can expose you to chemicals including Soots, Benzene, Lead, and Nickel (metallic), known to the State of California to cause cancer, and Lead and Benzene known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.		