

## Han3A RJ45 Hybrid Cat5 PFT 8+4p



Image is for illustration purposes only. Please refer to product description.

Part number	10 12 005 1002
Specification	Han3A RJ45 Hybrid Cat5 PFT 8+4p
HARTING eCatalogue	<a href="https://b2b.harting.com/10120051002">https://b2b.harting.com/10120051002</a>

### Identification

Category	Connectors
Series	RJ45 Hybrid
Element	Panel feed through
Specification	Straight

### Version

Size	Han <sup>®</sup> 3 A
Number of contacts	8
further contacts	4x 48 V

### Technical characteristics

Limiting temperature	-40 ... +70 °C
Mating cycles	≥500
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s

### Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	Grey
RoHS	compliant with exemption



## Material properties

RoHS exemptions	6(a) / 6(a)-I: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight / Lead as an alloying element in steel for machining purposes containing up to 0,35 % lead by weight and in batch hot dip galvanised steel components containing up to 0,2 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

## Specifications and approvals

Approvals	DNV GL
PROFINET	Yes

## Commercial data

Packaging size	1
Net weight	62.5 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440101 Rectangular connectors (set)