

CUC-IND-J1ST-A/R4LS-PG-S - RJ45 PCB connectors



1321248

<https://www.phoenixcontact.com/us/products/1321248>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



RJ45 PCB connectors, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, material: Metal, connection method: THR reflow/THT wave, cable outlet: straight, Shortened contacts for an optimized THR soldering process

Your advantages

- Ideal for demanding applications due to the high shock and vibration resistance as well as the extended temperature range
- 360° shielding ensures reliable transmission, even in industrial applications
- Housing shield springs enable an optimized EMC shielding concept
- Enables data transmission rates of up to 10 Gbps
- Automated handling process thanks to reflow capability
- The extended temperature range from -40°C to +105°C enables use in demanding industrial applications
- Tape-on-reel packaging

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1321248 |
| Packing unit | 84 pc |
| Minimum order quantity | 84 pc |
| Sales key | AB12 |
| Product key | ABNADA |
| GTIN | 4063151608316 |
| Weight per piece (including packing) | 9.18 g |
| Weight per piece (excluding packing) | 9.1 g |
| Customs tariff number | 85366930 |
| Country of origin | CN |

1321248

<https://www.phoenixcontact.com/us/products/1321248>

Technical data

Product properties

| | |
|-----------------------------|------------------------------|
| Product type | Data connector (device side) |
| Type | RJ45 |
| Number of positions | 8 |
| Connection profile | RJ45 |
| Type of packaging | Tape and Reel |
| [W] tape width | 44.00 mm |
| [A] coil diameter | 330.00 mm |
| [W2] coil overall dimension | 50.40 mm |
| Housing shield springs | Yes |
| Number of slots | 1 |
| Type | Socket |
| Shielded | yes |
| Cable outlet | straight |

Insulation characteristics

| | |
|----------------------|---|
| Overvoltage category | I |
| Degree of pollution | 2 |

Electrical properties

| | |
|-----------------------------|------------------|
| Rated voltage (III/2) | 72 V DC |
| Rated surge voltage | 1.5 kV DC |
| Rated surge voltage (III/3) | 1.5 kV |
| Rated surge voltage | 1 kV DC |
| Rated current | 1.5 A |
| Frequency range | 10 Hz ... 500 Hz |
| Insulation resistance | > 500 MΩ |
| Test voltage | 1 kV DC |
| Test voltage Core/Core | 1 kV DC |
| Test voltage Core/Shield | 1.50 kV DC |
| Transmission medium | Copper |
| Transmission speed | 10 Gbps |
| Power transmission | PoE++ |

Connection data

Connection technology

| | |
|-------------------|---------------------|
| Connection method | THR reflow/THT wave |
|-------------------|---------------------|

Dimensions

| | |
|--------|---------|
| Width | 18 mm |
| Height | 17.6 mm |

1321248

<https://www.phoenixcontact.com/us/products/1321248>

| | |
|------------------|----------|
| Length | 17.1 mm |
| Installed height | 12.80 mm |
| Orientation to | 90.00 ° |
| Data pin length | 2.00 mm |

Material specifications

| | |
|--|--------------------|
| Material | Au (1,27 µm/50 µ") |
| | Ni |
| | Au |
| | Ni |
| | Copper alloy |
| Flammability rating according to UL 94 | V0 |
| Housing material | Metal |
| Housing surface material | Nickel |
| Contact material | Copper alloy |
| Contact surface material | Gold |

Cable/line

| | |
|--------------------------|------------|
| Test voltage Core/Core | 1 kV DC |
| Test voltage Core/Shield | 1.50 kV DC |
| Halogen-free | yes |

Mechanical properties

Mechanical data

| | |
|-------------------------------------|-----------|
| Insertion/withdrawal cycles | > 750 |
| Insertion force per signal contact | < 20.00 N |
| Extraction force per signal contact | < 20 N |

Environmental and real-life conditions

Test specification

| | |
|---------------|------------------------|
| Frequency | 10-500 Hz |
| Sweep speed | 1 octave/min |
| Amplitude | 0.35 mm |
| Acceleration | 50.00 m/s ² |
| Test duration | 20.00 s |

Test specification

| | |
|---------------|-------------------------|
| Specification | IEC60068-2-27 |
| Acceleration | 295.00 m/s ² |

Ambient conditions

| | |
|---|-------------------|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 105 °C |
| Ambient temperature (storage/transport) | -40 °C ... 105 °C |

CUC-IND-J1ST-A/R4LS-PG-S - RJ45 PCB connectors



1321248

<https://www.phoenixcontact.com/us/products/1321248>

Mounting


| | |
|---|---------------|
| Mounting type | THR soldering |
| Processing notes | |
| Moisture Sensitive Level | MSL 2 |
| Classification temperature T _c | 260 °C |
| Solder cycles in the reflow | 3 |

1321248


<https://www.phoenixcontact.com/us/products/1321248>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1321248>



cUL Recognized
Approval ID: FILE E 335024



UL Recognized
Approval ID: FILE E 335024

cULus Recognized

1321248

<https://www.phoenixcontact.com/us/products/1321248>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440223 |
| ECLASS-12.0 | 27440223 |
| ECLASS-13.0 | 27460201 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC003557 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

Environmental product compliance

| | |
|---|--|
| EU RoHS | |
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

CUC-IND-J1ST-A/R4LS-PG-S - RJ45 PCB connectors



1321248

<https://www.phoenixcontact.com/us/products/1321248>

Accessories

CUC-IND-C1ZNI-S/R4IE10G8 - RJ45 connector

1149846

<https://www.phoenixcontact.com/us/products/1149846>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: straight, color: yellow, Ethernet

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector

1149847

<https://www.phoenixcontact.com/us/products/1149847>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 23- 22, cable outlet: straight, color: yellow, Ethernet

CUC-IND-J1ST-A/R4LS-PG-S - RJ45 PCB connectors



1321248

<https://www.phoenixcontact.com/us/products/1321248>

CUC-IND-C1ZNI-S/R4IP8 - RJ45 connector

1421126

<https://www.phoenixcontact.com/us/products/1421126>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 23- 22, cable outlet: straight, color: green, Ethernet/PROFINET

CUC-IND-C1ZNI-S/R4IE8 - RJ45 connector

1421607

<https://www.phoenixcontact.com/us/products/1421607>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: straight, color: green, Ethernet

CUC-IND-J1ST-A/R4LS-PG-S - RJ45 PCB connectors



1321248

<https://www.phoenixcontact.com/us/products/1321248>

CUC-IND-C1ZNI-S/R4QV6 - RJ45 connector

1406335

<https://www.phoenixcontact.com/us/products/1406335>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 6, 100 Mbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: straight, High degree of resistance to vibration; 360° shielding; one-piece design; special tool-free assembly, VARAN

CUC-IND-C1ZNI-T/R4IE8 - RJ45 connector

1421877

<https://www.phoenixcontact.com/us/products/1421877>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: angled, Ethernet

CUC-IND-J1ST-A/R4LS-PG-S - RJ45 PCB connectors



1321248

<https://www.phoenixcontact.com/us/products/1321248>

CUC-IND-C1ZNI-B/R4IE8 - RJ45 connector

1421876

<https://www.phoenixcontact.com/us/products/1421876>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: angled, Ethernet

CUC-IND-C1ZNI-B/R4QV6 - RJ45 connector

1406338

<https://www.phoenixcontact.com/us/products/1406338>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 6, 100 Mbps, CAT5 (IEC 11801:2002), material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: angled, High degree of resistance to vibration; 360° shielding; one-piece design; special tool-free assembly, VARAN

CUC-IND-J1ST-A/R4LS-PG-S - RJ45 PCB connectors



1321248

<https://www.phoenixcontact.com/us/products/1321248>

CUC-IND-C1ZNI-T/R4QV6 - RJ45 connector

1406341

<https://www.phoenixcontact.com/us/products/1406341>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 6, 100 Mbps, CAT5 (IEC 11801:2002), material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: angled, High degree of resistance to vibration; 360° shielding; one-piece design; special tool-free assembly, VARAN

CUC-IND-C1ZNI-B/R4IP8 - RJ45 connector

1421127

<https://www.phoenixcontact.com/us/products/1421127>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 23- 22, cable outlet: angled, Ethernet/PROFINET

CUC-IND-J1ST-A/R4LS-PG-S - RJ45 PCB connectors



1321248

<https://www.phoenixcontact.com/us/products/1321248>

CUC-IND-C1ZNI-T/R4IP8 - RJ45 connector

1421128

<https://www.phoenixcontact.com/us/products/1421128>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 23- 22, cable outlet: angled, Ethernet/PROFINET

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com