

1337254

https://www.phoenixcontact.com/us/products/1337254

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

RJ45 PCB connectors, degree of protection: IP20, number of positions: 8, 10 Gbps, material: Metal, connection method: THR reflow/THT wave



#### Your advantages

- · The right version for every application. Available with and without LED, single- and multi-port
- · The reflow capability enables efficient, cost-optimized processing
- · High standoffs allow ideal thermal airflow during processing
- · Tape-on-reel packaging is perfect for automated processing
- The extended temperature range from -50 °C ... +85 °C enables use in demanding applications
- Through-hole technology (THT) provides high mechanical stability when connecting the female connector to the PCB

#### Commercial data

Item number	1337254
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	AB12
Product key	ABNADA
GTIN	4063151638450
Weight per piece (including packing)	10.64 g
Weight per piece (excluding packing)	10.64 g
Customs tariff number	85366930
Country of origin	CN



1337254

https://www.phoenixcontact.com/us/products/1337254

#### Technical data

### Product properties

Product type	Data connector (device side)
Туре	RJ45
Number of positions	8
Connection profile	RJ45
Type of packaging	Tape and Reel
[W] tape width	56.00 mm
[A] coil diameter	330.00 mm
[W2] coil overall dimension	61.10 mm
Housing shield springs	Yes
Number of slots	2
Туре	Socket
Shielded	yes
LED	yes
Insulation characteristics	
Overvoltage category	I I

2

#### Electrical properties

Degree of pollution

Rated voltage (III/2)	72 V DC
Rated surge voltage	1.5 kV DC
Rated surge voltage (III/3)	1.5 kV
Rated surge voltage	1 kV DC
Rated current	1.5 A
Frequency range	10 Hz 500 Hz
Insulation resistance	> 500 MΩ
Test voltage	1 kV DC
Test voltage Core/Core	1 kV DC
Test voltage Core/Shield	1.50 kV DC
Transmission medium	Copper
Transmission speed	10 Gbps
Power transmission	PoE++

#### Connection data

#### Connection technology

Connection method	THR reflow/THT wave

#### **Dimensions**

Width	35.5 mm
Height	18.2 mm



1337254

https://www.phoenixcontact.com/us/products/1337254

Length	16.5 mm
Installed height	13.60 mm
Orientation to	90.00 °
Data pin length	2.00 mm

#### Material specifications

Material	Au (1,27 μm/50 μ")
	Sn (2.54 μm/100 μ")
	Ni (1.27 μm/50 μ")
	Ni (1.27 μm/50 μ")
	Stainless steel
	LCP
Flammability rating according to UL 94	V0
Housing material	Metal
Contact material	Phosphor bronze
Contact surface material	Gold over nickel
Contact carrier material	LCP

#### Cable/line

Test voltage Core/Core	1 kV DC
Test voltage Core/Shield	1.50 kV DC
Halogen-free	yes

#### Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	> 750
Insertion force per signal contact	< 20.00 N
Extraction force per signal contact	< 20 N

#### Environmental and real-life conditions

#### Test specification

Frequency	10-500 Hz
Sweep speed	1 octave/min
Amplitude	0.35 mm
Acceleration	50.00 m/s²
Test duration	20.00 s

#### Test specification

Specification	IEC60068-2-27
Acceleration	295.00 m/s²

#### Ambient conditions

Ambient Conditions		
	Degree of protection	IP20
	Ambient temperature (operation)	-50 °C 85 °C



1337254

https://www.phoenixcontact.com/us/products/1337254

Ambient temperature (storage/transport)	-40 °C 85 °C
Mounting	
Mounting type	PCB mounting
Processing notes	
Process	THR
Moisture Sensitive Level	MSL 1
Classification temperature T <sub>c</sub>	260 °C
Solder cycles in the reflow	3



1337254

https://www.phoenixcontact.com/us/products/1337254

#### **Approvals**

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1337254



**UL Recognized**Approval ID: FILE E 335024



1337254

https://www.phoenixcontact.com/us/products/1337254

### Classifications

#### **ECLASS**

ECLASS-11.0	27440390
ECLASS-12.0	27440390
ECLASS-13.0	27460201

#### **UNSPSC**

UNSPSC 21.0	39121400



1337254

https://www.phoenixcontact.com/us/products/1337254

### Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



1337254

https://www.phoenixcontact.com/us/products/1337254

#### Accessories

VS-08-RJ45-10G/Q - RJ45 connector

1419001

https://www.phoenixcontact.com/us/products/1419001



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6 $_{\rm A}$ , material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: straight, color: black, Ethernet

#### VS-08-RJ45-5-Q/IP20 - RJ45 connector

1656725

https://www.phoenixcontact.com/us/products/1656725



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 23, cable outlet: straight, color: traffic grey A RAL 7042, Ethernet



1337254

https://www.phoenixcontact.com/us/products/1337254

#### VS-08-RJ45-5-Q/IP20 BK - RJ45 connector

1658008

https://www.phoenixcontact.com/us/products/1658008



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 23, cable outlet: straight, color: black, Ethernet

#### VS-PN-RJ45-5-Q/IP20 - RJ45 connector

1658435

https://www.phoenixcontact.com/us/products/1658435



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 4, 100 Mbps, CAT5, material: Plastic, connection method: Insulation displacement connection, cable outlet: straight, color: traffic grey A RAL 7042, PROFINET



1337254

https://www.phoenixcontact.com/us/products/1337254

#### CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector

1149847

https://www.phoenixcontact.com/us/products/1149847



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6<sub>A</sub>, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 23- 22, cable outlet: straight, color: yellow, Ethernet

#### CUC-IND-C1ZNI-S/R4IE10G8 - RJ45 connector

1149846

https://www.phoenixcontact.com/us/products/1149846



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps,  $CAT6_A$ , material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: straight, color: yellow, Ethernet



1337254

https://www.phoenixcontact.com/us/products/1337254

#### CUC-IND-C1ZNI-S/R4IP8 - RJ45 connector

1421126

https://www.phoenixcontact.com/us/products/1421126



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 23- 22, cable outlet: straight, color: green, Ethernet/PROFINET

#### CUC-IND-C1ZNI-S/R4IE8 - RJ45 connector

1421607

https://www.phoenixcontact.com/us/products/1421607



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: straight, color: green, Ethernet



1337254

https://www.phoenixcontact.com/us/products/1337254

#### CUC-IND-C1ZNI-B/R4IP8 - RJ45 connector

1421127

https://www.phoenixcontact.com/us/products/1421127



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 23- 22, cable outlet: angled, Ethernet/PROFINET

#### CUC-IND-C1ZNI-B/R4IE8 - RJ45 connector

1421876

https://www.phoenixcontact.com/us/products/1421876



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: angled, Ethernet



1337254

https://www.phoenixcontact.com/us/products/1337254

#### CUC-IND-C1ZNI-T/R4IP8 - RJ45 connector

1421128

https://www.phoenixcontact.com/us/products/1421128



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 23- 22, cable outlet: angled, Ethernet/PROFINET

#### CUC-IND-C1ZNI-T/R4IE8 - RJ45 connector

1421877

https://www.phoenixcontact.com/us/products/1421877



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: angled, Ethernet

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com