

HanPP V14 RJ45 GL Cat6A plug 8p




Image is for illustration purposes only. Please refer to product description.

Part number	09 35 227 0421
Specification	HanPP V14 RJ45 GL Cat6A plug 8p
HARTING eCatalogue	https://b2b.harting.com/09352270421

Identification

Category	Connectors
Series	Han [®] PushPull (V14)
Identification	RJ45
Element	Connector sets
Features	Intuitive locking mechanism

Version

Termination method	Piercing termination
Shielding	Fully shielded, 360° shielding contact
Number of contacts	8
Locking type	PushPull
Pack contents	incl. housing and male insert

Technical characteristics

Conductor cross-section	0.1 ... 0.22 mm ² Stranded 0.26 ... 0.32 mm ² Solid
Conductor cross-section	AWG 28/7 ... AWG 24/7 Stranded
Wire outer diameter	≤1.05 mm
Rated current	1.75 A
Rated voltage	50 V
Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz



Pushing Performance
 Since 1945

Technical characteristics

Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s
Limiting temperature	-40 ... +70 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65
	IP67
Clamping range	6.5 ... 9.5 mm

Material properties

Surface (contacts)	Au over Ni Mating side
	Sn over Ni Termination side
Material (hood/housing)	Thermoplastic
Colour (hood/housing)	Black
Material (O-ring)	NBR
Material (cable seal)	TPE
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead
	Nickel
	Naphthalene

Specifications and approvals

Specifications	IEC 61076-3-117 Variant 14 (V14)
	IEC 60603-7 Mating face
	EN 45545-2
UL / CSA	UL 1977 ECBT2.E102079
	CSA-C22.2 No. 182.3 ECBT8.E102079



Pushing Performance
Since 1945

Specifications and approvals

Approvals	DNV GL
PROFINET	Yes

Commercial data

Packaging size	10
Net weight	22.14 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140054127
ETIM	EC002636
eCl@ss	27440114 Rectangular connector (for field assembly)