

# RJI RJ45 PN plug Cat5, 4p IDC straight



Part number	09 45 151 1120
Specification	RJI RJ45 PN plug Cat5, 4p IDC straight
HARTING eCatalogue	https://b2b.harting.com/09451511120

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Connectors
Series	HARTING RJ Industrial <sup>®</sup>
Element	Cable connector
Specification	Straight

#### Version

Termination method	IDC termination
Shielding	Fully shielded, 360° shielding contact
Number of contacts	4

### Technical characteristics

Conductor cross-section	0.1 0.32 mm <sup>2</sup>
Conductor cross-section	AWG 27/7 AWG 22/7 Stranded AWG 27/1 AWG 22/1 Solid
Wire outer diameter	1.6 mm
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 +70 °C
Relative humidity	95 % Non-condensing (operation)
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP20
Cable diameter	4.5 9 mm



## Material properties

Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	Black
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel
Requirement set with Hazard Levels	R26

# Specifications and approvals

Specifications	EN 45545-2
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
Approvals	DNV GL
PROFINET	Yes

# Commercial data

Packaging size	10
Net weight	24.5 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140059351
ETIM	EC002636
eCl@ss	27440114 Rectangular connector (for field assembly)