

STARTER, 3RE41215CA311FB0, WITH MODS



product brand name	Siemens
product designation	Non-reversing motor starter
special product feature	Start-Stop Push Buttons
General technical data	
weight [lb]	14 lb
Height x Width x Depth [in]	12 × 10 × 6 in
touch protection against electrical shock	NA for enclosed products
installation altitude [ft] at height above sea level maximum	6 560 ft
country of origin	Germany
Power and control electronics	
number of poles for main current circuit	3
type of voltage of the control supply voltage	AC
control supply voltage	
• at AC at 50 Hz rated value	110 V
• at AC at 60 Hz rated value	120 V
disconnecter functionality	No
yielded mechanical performance [hp] for 3-phase AC motor	
• at 200/208 V rated value	1.5 hp
• at 220/230 V rated value	2 hp
• at 460/480 V rated value	3 hp
• at 575/600 V rated value	5 hp
Contactors	
number of NO contacts for main contacts	3
operating voltage for main current circuit at AC at 60 Hz maximum	600 V
operating voltage at AC-3 rated value maximum	600 V
mechanical service life (operating cycles) of the main contacts typical	30 000 000
Auxiliary contact	
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	1
number of total auxiliary contacts maximum	6
contact rating of auxiliary contacts of contactor according to UL	10A@600V(A600), 2.5A@600V(Q600)
Coil	
apparent pick-up power of magnet coil at AC	26.4 VA
apparent holding power of magnet coil at AC	4.4 VA
operating range factor control supply voltage rated value of magnet coil	0.8 ... 1.1
ON-delay time	9 ... 35 ms
OFF-delay time	3.5 ... 14 ms
Overload relay	

product function				
• overload protection				Yes
• test function				Yes
• external reset				Yes
reset function				Manual, automatic and remote (with optional accessory)
adjustment range of thermal overload trip unit				3.5 ... 5
number of NC contacts of auxiliary contacts of overload relay				1
number of NO contacts of auxiliary contacts of overload relay				1
contact rating of auxiliary contacts of overload relay according to UL				5A@600VAC (B600), 1A@250VDC (R300)
Enclosure				
degree of protection NEMA rating of the enclosure				NEMA 3/3R/4/12 enclosure
design of the housing				Dust- & watertight for outdoor use
Mounting/wiring				
mounting position				vertical
fastening method				Surface mounting and installation
type of electrical connection for supply voltage line-side				Screw-type terminals
tightening torque [lbf-in] for supply				7 ... 10 lbf-in
type of connectable conductor cross-sections at line-side for AWG cables single or multi-stranded				2x (20 ... 16), 2x (18 ... 14), 2x 12
temperature of the conductor for supply maximum permissible				60 °C
material of the conductor for supply				CU
type of electrical connection for load-side outgoing feeder				Screw-type terminals
tightening torque [lbf-in] for load-side outgoing feeder				7 ... 10 lbf-in
type of connectable conductor cross-sections for AWG cables for load-side outgoing feeder single or multi-stranded				2x (20 ... 16), 2x (18 ... 14), 2x 12
temperature of the conductor for load-side outgoing feeder maximum permissible				60 °C
material of the conductor for load-side outgoing feeder				CU
type of electrical connection of magnet coil				Screw-type terminals
tightening torque [lbf-in] at magnet coil				7 ... 10 lbf-in
type of connectable conductor cross-sections of magnet coil for AWG cables single or multi-stranded				2x (20 ... 16), 2x (18 ... 14), 2x 12
temperature of the conductor at magnet coil maximum permissible				75 °C
material of the conductor at magnet coil				CU
type of electrical connection for auxiliary contacts				Screw-type terminals
tightening torque [lbf-in] at contactor for auxiliary contacts				7 ... 10 lbf-in
type of connectable conductor cross-sections at contactor for AWG cables for auxiliary contacts single or multi-stranded				2x (20 ... 16), 2x (18 ... 14), 2x 12
temperature of the conductor at contactor for auxiliary contacts maximum permissible				75 °C
material of the conductor at contactor for auxiliary contacts				CU
type of electrical connection at overload relay for auxiliary contacts				Screw-type terminals
tightening torque [lbf-in] at overload relay for auxiliary contacts				7 ... 10 lbf-in
type of connectable conductor cross-sections at overload relay for AWG cables for auxiliary contacts single or multi-stranded				2x (20 ... 16), 2x (18 ... 14)
temperature of the conductor at overload relay for auxiliary contacts maximum permissible				70 °C
material of the conductor at overload relay for auxiliary contacts				CU
Short-circuit current rating				
design of the fuse link for short-circuit protection of the main circuit required				Class J
design of the short-circuit trip				Thermal magnetic circuit breaker
maximum short-circuit current breaking capacity (Icu)				
• at 240 V				5 kA
• at 480 V				5 kA
• at 600 V				5 kA
certificate of suitability				UL 60947-4-1
Approvals Certificates				
General Product Approval	Test Certificates	other	Dangerous Good	Environment



[Confirmation](#)

[Transport Information](#)

[Environmental Con-
firmations](#)

Further information

Industrial Controls - Product Overview (Catalogs, Brochures,...)

www.usa.siemens.com/iccatalog

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=3RE4121-5CA31-1FB0>

Search Datasheet in Service&Support (Manuals)

<https://support.industry.siemens.com/cs/US/en/ps/3RE4121-5CA31-1FB0/man>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RE4121-5CA31-1FB0&lang=en

Certificates/approvals

<https://support.industry.siemens.com/cs/US/en/ps/3RE4121-5CA31-1FB0/certificate>



last modified:

4/15/2021 