

BMH1902P31F2A

servo motor BMH, Lexium 32, 48Nm, 4000rpm,
keyed shaft, with brake, IP65, IP67, 128bit
encoder





Main

Device short name	BMH
Product or Component Type	Servo motor
Maximum mechanical speed	4000 rpm
Continuous stall torque	331.02 Lbf.In (37.4 N.m) LXM32.D72N4 24 A, 400 V, three phase 331.02 Lbf.In (37.4 N.m) LXM32.D72N4 24 A, 480 V, three phase 424.8 Lbf.In (48 N.m) LXM32MD85N4 32 A, 400 V, three phase 424.8 Lbf.In (48 N.m) LXM32MD85N4 32 A, 480 V, three phase 424.8 Lbf.In (48 N.m) LXM32MC10N4 40 A, 400 V, three phase 424.8 lbf.in (48 N.m) LXM32MC10N4 40 A, 480 V, three phase
Peak stall torque	893.9 Lbf.In (101 N.m) LXM32.D72N4 24 A, 400 V, three phase 893.9 Lbf.In (101 N.m) LXM32.D72N4 24 A, 480 V, three phase 1022.3 Lbf.In (115.5 N.m) LXM32MD85N4 32 A, 400 V, three phase 1022.3 Lbf.In (115.5 N.m) LXM32MD85N4 32 A, 480 V, three phase 1156.8 Lbf.In (130.7 N.m) LXM32MC10N4 40 A, 400 V, three phase 1156.8 lbf.in (130.7 N.m) LXM32MC10N4 40 A, 480 V, three phase
Nominal output power	5900 W LXM32.D72N4 24 A, 400 V, three phase 5900 W LXM32.D72N4 24 A, 480 V, three phase 6070 W LXM32MD85N4 32 A, 400 V, three phase 6070 W LXM32MD85N4 32 A, 480 V, three phase 6070 W LXM32MC10N4 40 A, 400 V, three phase 6070 W LXM32MC10N4 40 A, 480 V, three phase
Nominal torque	197.4 Lbf.In (22.3 N.m) LXM32.D72N4 24 A, 400 V, three phase 197.4 Lbf.In (22.3 N.m) LXM32.D72N4 24 A, 480 V, three phase 256.7 Lbf.In (29 N.m) LXM32MD85N4 32 A, 400 V, three phase 256.7 Lbf.In (29 N.m) LXM32MD85N4 32 A, 480 V, three phase 256.7 Lbf.In (29 N.m) LXM32MC10N4 40 A, 400 V, three phase 256.7 lbf.in (29 N.m) LXM32MC10N4 40 A, 480 V, three phase
Nominal speed	2000 rpm LXM32MC10N4 40 A, 400 V, three phase 2000 rpm LXM32MC10N4 40 A, 480 V, three phase 2500 rpm LXM32.D72N4 24 A, 400 V, three phase 2500 rpm LXM32.D72N4 24 A, 480 V, three phase 2000 rpm LXM32MD85N4 32 A, 400 V, three phase 2000 rpm LXM32MD85N4 32 A, 480 V, three phase
Product compatibility	LXM32.D72N4 400...480 V three phase
Shaft end	Keyed
IP Degree of Protection	IP65 standard IP67 with IP67 kit
Speed feedback resolution	131072 points/turn
Holding brake	With
Mounting Support	International standard flange
Electrical Connection	Rotatable right-angled connectors

Complementary

Range Compatibility	Lexium 32
[Us] rated supply voltage	480 V
Phase	Three phase
Continuous stall current	30.8 A
Continuous power	6.1 W
Maximum current Irms	72 A LXM32.D72N4
Maximum permanent current	114 A
Second shaft	Without second shaft end
Shaft diameter	1.5 in (38 mm)
Shaft length	3.1 in (80 mm)
Key width	2.8 in (70 mm)
Feedback type	Single turn SinCos Hiperface
Holding torque	708.06 lbf.in (80 N.m) holding brake
Motor flange size	7.5 in (190 mm)
Number of motor stacks	2
Torque constant	1.56 N.m/A 248 °F (120 °C)
Back emf constant	108.3 V/krpm 248 °F (120 °C)
Number of motor poles	10
Rotor inertia	144.8 kg.cm ²
Stator resistance	0.15 Ohm 68 °F (20 °C)
Stator inductance	3.86 mH 68 °F (20 °C)
Stator electrical time constant	25.7 ms 68 °F (20 °C)
Maximum radial force Fr	4200 N 1000 rpm
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	40 W
Type of cooling	Natural convection
Length	12.2 in (310 mm)
Centring collar diameter	7.09 in (180 mm)
Centring collar depth	0.2 in (4 mm)
Number of mounting holes	4
Mounting holes diameter	0.6 in (14 mm)
Circle diameter of the mounting holes	8.5 in (215 mm)
Net Weight	71.7 lb(US) (32.5 kg)

Ordering and shipping details

Category	US1PC5318282
Discount Schedule	PC53
GTIN	3606485264172
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.8 in (30.0 cm)
Package 1 Width	15.7 in (40.0 cm)
Package 1 Length	31.3 in (79.5 cm)
Package 1 Weight	69.4 lb(US) (31.5 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------