



**CONFIDENTIAL & PROPRIETARY INFORMATION**

This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM



**NOTES:**

- MAGNET PROPERTIES PER N-35H:  
 Br: 11,700-12,200 G  
 Hc: 11,000-11,900 Oe  
 Hci: ≥17,000 Oe  
 T max: 120 C
- SUPPLIED MAGNETIZED ACROSS THE DIAMETER
- PARTS ARE NICKEL PLATED FOR MIN 15hrs SALT SPRAY



REV	DESCRIPTION	DATE	BY
A	Released for production	5/07/21	BT

**TOLERANCES**  
(UNLESS OTHERWISE NOTED)

DECIMAL      METRIC  
 X.XX = ± .01    X.X = ± .25  
 X.XXX = ± .005   X.XX = ± .13

**ANGLES**  
 ± .5°

DO NOT SCALE DRAWING

<b>Alliance LLC</b>		
1450 CLARK DRIVE, VALPARAISO, INDIANA 46385		
DESCRIPTION: 8.0 mm x 3.0 mm DISC MAGNET		
<b>AN5000 SENSOR MAGNET</b>		<b>P/N: ALC8300</b>
GRADE: N-35H	Drwg by: BT	REV LEVEL: A
COATING: Nickel	Appr by: DV	Appr. Dated: 05-08-2021