207437-3 🗸 ACTIVE

TE Internal #: 207437-3 Socket Contact, Tin, 250 VAC, Locking Lance Contact Retention, Discrete Wire, 28 - 22 AWG Wire Size, .08 - .34 mm² Wire Size, Crimp, Brass, Signal

View on TE.com >



Connectors > Contacts > Connector Contacts



Contact Type: Socket

Contact Mating Area Plating Material: Tin

Wire Contact Termination Area Plating Material: None

Operating Voltage: 250 VAC

Contact Retention Within Housing: With

Features

Configuration Features

COLLING		Cului	
\sim			

Compatible With Wire & Cable Type	Discrete Wire			
Electrical Characteristics				
Operating Voltage	250 VAC			
Contact Features				
Contact Diameter	1.93 mm			
Contact Type	Socket			
Contact Mating Area Plating Material	Tin			
Wire Contact Termination Area Plating Material	None			
Contact Retention Within Housing	With			
Contact Base Material	Brass			
Contact Current Rating (Max)	10 A			
Termination Features				
Termination Method to Wire & Cable	Crimp			
Product Terminates To	Wire & Cable			

207437-3

Socket Contact, Tin, 250 VAC, Locking Lance Contact Retention, Discrete Wire, 28 - 22 AWG Wire Size, .08 - .34 mm² Wire Size, Crimp, Brass, Signal



Mechanical Attachment

Contact Retention Type Within Housing	Locking Lance
Dimensions	
Compatible Insulation Diameter Range	.91 - 1.37 mm[.036054 in]
Wire Size	.0834 mm²
Usage Conditions	
Operating Temperature Range	-55 - 105 °C[-67 - 221 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Method	Loose Piece
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant

EU ELV Directive 2000/53/EC

China RoHS 2 Directive MIIT Order No 32, 2016

Compliant

No Restricted Materials Above Threshold

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

207437-3

Socket Contact, Tin, 250 VAC, Locking Lance Contact Retention, Discrete Wire, 28 -22 AWG Wire Size, .08 - .34 mm² Wire Size, Crimp, Brass, Signal



Compatible Parts



Customers Also Bought



Documents

Product Drawings CONTACT, SOCKET

English

CAD Files 3D PDF

English

Customer View Model

ENG_CVM_207437-3_G.3d_igs.zip

English

Customer View Model

ENG_CVM_207437-3_G.3d_stp.zip

English

Customer View Model

ENG_CVM_207437-3_G.2d_dxf.zip

English

3D PDF

3D

Customer View Model ENG_CVM_CVM_207437-3_AE.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_207437-3_AE.3d_igs.zip

207437-3

Socket Contact, Tin, 250 VAC, Locking Lance Contact Retention, Discrete Wire, 28 - 22 AWG Wire Size, .08 - .34 mm² Wire Size, Crimp, Brass, Signal



English

Customer View Model ENG_CVM_CVM_207437-3_AE.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Application and Maintenance for Hand Crimping Tool

English