

Product: <u>10GXW13</u> ⊠ 10GXW (0.250") Category 6A Cable, 4 Pair, U/UTP, CMP

Product Description

10GXW (0.250" Diameter) Category 6A Premise Horizontal Cable (500MHz), 4 Pair, 23 AWG Solid Bare Copper Conductors, U/UTP, Plenum-CMP, Flamarrest® PVC-LS Jacket

Technical Specifications

Ŷ

Product Overview

| Suitable Applications: | Premise Horizontal Cable, Ethernet 10GBASE-T, Wi-Fi 6, Wi-Fi 5, In-Building Wireless, In-Building Small Cells, Mobile RAN, PoE++, PoE+, PoE+, HDBaseT |
|------------------------|---|
| Patent: | This product has one or more applicable patents. More information on patents can be found at https://www.belden.com/patents. |

Construction Details

| Conducto | r | | |
|----------|-----------|------------------|-----------|
| Size | Stranding | Material | No. of Pa |
| 23 AWG | Solid | BC - Bare Copper | 4 |

Insulation

| Material | Color Code |
|--------------------------------------|--|
| FEP - Fluorinated Ethylene Propylene | White & Blue, White & Orange, White & Green, White & Brown |

airs

Outer Jacket

| Separator | | Material | Material Trade Name | Nom. Diameter | Ripcord |
|--------------------------------------|--|--------------------------|---------------------|--------------------|---------|
| Center Member (Patented X-Sp | oline®), EquiBlock™ Barrier Technology | PVC - Polyvinyl Chloride | Flamarrest® | 0.250 in (6.35 mm) | Yes |
| Overall Cable Diameter (Nominal): | 0.250 in (6.35 mm) | | | | |

Electrical Characteristics

Electricals

| Max. Conductor DCR | Max. Capacitance Unbalance |
|---------------------------|----------------------------|
| 82 Ohm/km (25 Ohm/1000ft) | 45 pF/100m |

Delay

| Max. Delay | Max. Delay Skew | Nom. Velocity of Prop. |
|---------------|-----------------|------------------------|
| 537.6 ns/100m | 45 ns/100m | 69% |

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

Temperature

| UL Temperature | Operating | Installation | Storage |
|----------------|----------------|--------------|----------------|
| 105°C | -20°C To +75°C | 0°C To +50°C | -20°C To +75°C |

Bend Radius

1 in (25 mm)

| Max. Pull Tension: | 25 lbs (11 kg) |
|--------------------|----------------|
| Bulk Cable Weight: | 34 lbs/1000ft |

Standards and Compliance

| Environmental Suitability: | Plenum, Indoor |
|-------------------------------------|---|
| Flammability / Reaction to Fire: | NFPA 262, UL 910 (Plenum), FT6 |
| NEC / UL Compliance: | Article 800, CMP, CMP-LP (0.5A), CL3P-LP (0.5A) |
| CEC / C(UL) Compliance: | СМР |
| ICEA Compliance: | S-116-732 |
| IEEE Compliance: | IEEE 802.3bt Type 1, Type 2, Type 3, Type 4 |
| NEMA Compliance: | ANSI/NEMA WC-66 |
| Data Category: | Category 6A |
| TIA/EIA Compliance: | ANSI/TIA-568.2-D Category 6A |
| ISO/IEC Compliance: | ISO/IEC 11801-1, IEC 61156-5 |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16 |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |

Product Notes

| | | Notes' | Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0. |
|--|--|--------|--|
|--|--|--------|--|

History

Update and Revision: Revision Number: 0.121 Revision Date: 05-31-2024

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.