



**Product:** [5582UG](#)

Security & Sound, #22-4c, BC, CM

## Product Description

Security & Sound Cable, Rated-CM, 4-22 AWG solid bare copper conductors with polyolefin insulation, PVC jacket

## Technical Specifications

### Product Overview

Suitable Applications:	Security System, Alarm, Intercom/PA, Single Line Telephone, Station Wire
------------------------	--

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors
22	Solid	BC - Bare Copper	4

Conductor Count:	4
------------------	---

#### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.006 in

#### Color Chart

Color
Black
Red
Yellow
Green

#### Outer Shield

Material
No Shield

#### Outer Jacket

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.122 in	0.015 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
15.7 Ohm/1000ft

#### Current

Max. Recommended Current [A]
2.2 Amps per Conductor at 25°C

#### Voltage

UL Voltage Rating
300 V RMS

## Temperature Range

UL Temp Rating:	75°C
Operating Temperature Range:	-20°C To +75°C

## Mechanical Characteristics

Bulk Cable Weight:	13 lbs/1000ft
Max. Pull Tension:	31.2 lbs
Min. Bend Radius/Minor Axis:	1.2 in

## Standards

NEC Articles:	Article 800
NEC/(UL) Compliance:	CM
CEC/C(UL) Compliance:	CM

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 UL Loading
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Related Part Numbers

### Variants

Item #	Color	UPC
5582UG U4FC1000	Beige U4F	612825164593
5582UG U4FC500	Beige U4F	612825164609
5582UG U4FU1000	Beige U4F	612825164616
5582UG 001C500	Brown	612825164623
5582UG 008C1000	Gray	612825164630
5582UG 008C500	Gray	612825164647
5582UG 009C1000	White	612825164654
5582UG 009C500	White	612825164661
5582UG 009U1000	White	612825164678

## History

Update and Revision:	Revision Number: 0.295 Revision Date: 05-05-2023
----------------------	--

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.