



RESISTANCE @ +25°C = 2,000 Ω ± 1%
 RESISTANCE/TEMPERATURE CURVE = SEE ED35S20F202 REV.1 R-T TABLE
 DISSIPATION CONSTANT = 1.5 mW/°C MINIMUM (AIR)
 THERMAL TIME CONSTANT = 15 SECONDS NOMINAL (AIR)
 MAXIMUM TEMPERATURE RATING = +150°C

ROHS COMPLIANT

PACKAGING: SEE TABLE

REV	DESCRIPTION	DATE	APP
1	MODIFIED R-T CHARACTERISTICS	07/21/2020	DD
0	INITIAL RELEASE	05/11/2020	DD

REVISION HISTORY

EI SENSOR TECHNOLOGIES www.ei-sensor.com © COPYRIGHT	PTC THERMISTOR	
	DRAWN BY: DAN DANKERT	
P/N ED35S20F202-	SCALE: NONE	LAYER: 0 OF 2
	REV: 1	DATE: 05/11/2020

This PROPRIETARY document is the property of EI Sensor Technologies. It is confidential in nature, non-transferrable and issued with the understanding that it is not to be traced or copied without permission, and is returnable on demand.

PART NUMBER	PACKAGING
ED35S20F202-B	BULK
ED35S20F202-T	TAPE & REEL PER IEC 60286-1